



www.lemo.com

SUMMARY

Wires

Triax

 Low
 0

 High
 0

 Coax
 1

Quad 0

Fiber 0
Fluidic 0

Series 01

Termination type Female solder

IP rating 50

 Cable Ø
 0.00 - 0.00 mm

 Matching parts
 FFS.01.250.DLAE24

0

Status active

Alternative part



Image is for illustrative purpose only

Download

Request a quote

Catalog

TECHNICAL DETAILS

Mechanics

Shell Style/Model PCS*: Free receptacle with cable crimping

Keying Circular (can rotate)

Housing Material Brass (gold plated) shell, collet nut, brass latch sleeve and mid pieces

Cable Fixing : 0 - 0 mm

Variant

Performance

Configuration 0.25 : 1 Coax (50 Ohm)

Insulator


Rated Current

Others

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

DRAWINGS

Draws



Dimensions

	А	L	S1	S2
mm.	5	18	4	4
in.	0,20	0,71	0,16	0,16

RECOMMENDED BY LEMO

Tools

None

Cables

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.