

# STATFREE® ESD ULTRA CLEAR BAG



Meets the required limits of ANSI/ESD S20.20, Packaging standard ANSI/ESD S541, and Static Control Bag standard ANSI/ESD S11.4 Level 5.

## **Specifications:**

Electrical Properties	Typical Value	Test Procedures/Method
Surface Resisitance:		
(Interior and Exterior)	$1 \times 10^4 \text{ to} < 1 \times 10^{11} \text{ ohms}$	per ANSI/ESD STM11.11
Charge Generation:	_	
Teflon	-0.10 (nC/in <sup>2</sup> ) +0.10 (nC/in <sup>2</sup> )	Modified Incline Plane
Quartz	+0.10 (nC/in <sup>2</sup> )	Modified Incline Plane

Physical Properties:		
Thickness	Nominal .0035" (.0889mm) ±10%	MIL-STD-3010, 1003
Width (Inside Dimensions)	Nominal -0" / + .125"	
Length (Inside Dimensions)	Nominal ± .125"	
Light Transmission	>90 (%)	STM D-1003
Heat Seal	>8 (lbs/in)	375°F, .75 sec 60 psi
Tensile Strength	>5,300 (MD/TD, psi)	ASTM D-882
Puncture Resistance	>14 lbs	MIL-STD-3010, 2065
Silicone	Not detected	FTIR
MVTR	0.35	ASTM F-1249

## ANSI/ESD S541 section 6.1 Inside an EPA

"Packaging used within an EPA (that satisfies the minimum requirements of ANSI/ESD S20.20) shall be:

- Low charge generation
- Dissipative or conductive materials for intimate contact"

### RoHS 2, REACH, and Conflict Minerals Statement

None of the RoHS 2 restricted materials or REACH substances of very high concern as of 2016/06/20, or Conflict Minerals are intentionally added in manufacturing this product. Ref: European Union Directive 2011/65/EU and Regulation (EC) No. 1907/2006/CE. See Desco Limited Warranty at Desco.com.

Statshield® and Statfree® are Registered Trademarks of Desco Industries Inc. See Bag Selection Chart Click HERE.



Specifications and procedures subject to change without notice.

STATFREE® ESD ULTRA CLEAR BAG WITH ZIPPER, .0035" (.0889mm)



Statshield® bags are packaged 100 per package in an oversized shielding bag.

See Shielding Bag Storage at TB-7057.

Mixed Unsortable Plastic Scrap

Mixed unsortable plastic scrap shall contain assorted plastics of multiple grades that are co-extruded, bonded or laminated together which are unsortable into individual grades Desco's bags are recyclable

> DESCO WEST: 3651 WALNUT AVE., CHINO, CA 91710 WEB SITE: Desco.com PHONE (909) 627-8178

DESCO EAST: ONE COLGATE WAY, CANTON, MA 02021-1407 PHONE (781) 821-8370

**DRAWING** NUMBER 13880

DATE: August 2016

Static Dissipative

48 GA Polyester

Static Dissipative

Permastat™ PE

Coating