

Data interface - SI-SES-U1A/0,6 - 1404514

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Service socket with USB (socket/plug), type A with 0.6 m cable



RoHS

Key Commercial Data

Packing unit	1 STK
GTIN	
GTIN	4046356698542

Technical data

Mechanical characteristics

Connection profile	USB-A
Shielded	yes
Insertion/withdrawal cycles	≥ 100
Cable diameter	6.10 mm
Length of cable	0.6 m

Ambient conditions

Ambient temperature (operation)	-5 °C ... 70 °C
Degree of protection	IP20 (when plugged in)
	IP65 (with closed protective cover)

Material data

Contact material	Copper alloy
Contact surface material	Au
Material	PA (Socket)
	PVC (Plug)

Electrical characteristics

Transmission speed	max. 5 Gbps (USB-A:3.0)
--------------------	-------------------------

Data interface - SI-SES-U1A/0,6 - 1404514


Technical data

Electrical characteristics

Degree of pollution	3
Rated voltage (III/3)	max. 30 V AC/DC (USB-A)

Drawings

Dimensional drawing



Approvals

Approvals

Approvals

EAC / EAC

Ex Approvals

Approval details

EAC		EAC-Zulassung
-----	--	---------------

EAC		RU C- DE.A*30.B.01102
-----	--	--------------------------

Phoenix Contact 2017 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>