



PIN Assignment		
P1		P2
1	WHITE	1
2	GREY	2
3	YELLOW	2
3	PINK	3
4	ORANGE	4
5	RED	5
6	BROWN	6
7	GREEN	7
8	BLUE	8
10	PURPLE	10
11	LIGHT GREEN	11
12	LIGHT BLUE	12
13	BLACK	13
14	WHITE/BLACK	14
15		15
Shell	DRAIN	Shell

Material:

- CABLE: NON-UL 28AWG(7/0.127)TC*14C INS:PVC+DRAIN WIRE(26AWG 7/0.16)+AL-FOIL/MYLAR
PVC JACKET COLOR:BEIGE, OD:6.0±0.2mm
- CONNECTOR:
P1&P2:HD15P MALE GOLD FLASH CONTACT,
NICKEL PLATED SHELL(THE 9TH PIN UNLOAD)
- HOOD:MOLDED TYPE PVC 45P COLOR:BEIGE.
- ELECTRICAL TEST:
<1>100% OPEN SHORT & MIS WIRE TEST.
<2>CONTACT RESISTANCE 3 Ohms MAX.
<3>INSULATION RESISTANCE 20M Ohms MIN.
- PACKING:SEE P-0039 REV.C PACKING DRAWING+EAN CODE
PACKING TYPE: DB VP4
(HANKING SIZE MUST BE SMALLER THAN PACKING)

Scale	1:1						Name	Item No.
TOLERANCE							Drawn	11.16.11
X.X	±0.40						Chappell	AK532-2 Title VGA Monitor Extension Cable, HD D-Sub 15 pin Male <=> Male, 2 Meters
X.XX	±0.25					Approved		
X.XXX	±0.15							
Angle	±3°							
								Drawing No.
								Replace
								Sheet

