

Ethernet-based, Modular Media Converters Chassis

MediaConverter/1



PRODUCT FEATURES

- Supports Ethernet, Fast Ethernet and Gigabit Ethernet
- Supports McPIMs, McLIMs, and McGigabit modules
- Table-top
- 1-slot chassis
- AC power
- Modular, hot-swappable architecture reduces operational costs associated with product installation, upgrades and maintenance

Your network is growing and many new access points, workstations, etc. are required. However, legacy equipment, along with your existing wiring infrastructure, must work with any new equipment you implement in your network. When copper-to-fiber conversions are required, along with advanced troubleshooting features, our MediaConverter/1 is the perfect solution.

The unmanaged B&B Electronics' MediaConverter/1 enables you to easily and cost-effectively connect one type of media to other dissimilar media or networking products. This series increases the functionality and extends the productive life of both your legacy cabling infrastructure and networking equipment when adding fiber to your network.

ORDERING INFORMATION

MODEL NUMBER	DESCRIPTION
MediaConverter/1	
851-10901	1 Slot, AC

ACCESSORIES

895-39949 - Rackmount Shelf

Ethernet-based, Modular Media Converters Chassis

MediaConverter/1



200

SPECIFICATIONS

TECHNICAL		
Single slot AC chassis to house the following modules: McPIM, McLIM, McLIM 10/100 and McGigabit		
MECHANICAL		
Dimensions	1.64"H x 4.75"W x 5.5"D (4.16cm H x 12.06cm W x 13.97cm D)	
Shipping Weight	2 lbs (.9 kg)	
POWER		
115/230 or 120-240 VAC. 50/60Hz. 0.3A/0.15A		

MECHANICAL DIAGRAM

(dimensions in inches)

ENVIRONMENTAL	
Operating Temperature: DC Terminal Block	+32° to +122° F (0° to +50° C)
Storage Temperature:	13° to +158° F (-25° to +70° C)
Operating Humidity	5% to 95% (non-condensing), 0 $-$ 10,000 ft. altitude
REGULATORY APPROVALS	
FCC Class A, UL/CUL, CE, CSA	



