

GEOCHEM



PROFESSIONAL
BUILDING
CHEMICAL
RANGE

FAST SET CEMENT

Geochem Fast Set Cement is specially designed cement which sets quickly in approximately 20 minutes enabling fast repairs and fixing etc. It can be used for permanent repairs to stone, brick, concrete, render and sanitary fittings.

Geochem Fast Set Cement is ideal for use in any situation where the minimum of delay and work disruption is required.

Geochem Fast Set Cement:

- Mortar for crack repairs
- For internal and external use
- For permanent repairs to stone, brick, concrete, render and sanitary fittings
- Installation of sanitary fittings and pipe grouting
- Sets hard in 20 minutes
- Non shrinking
- High strength



TECHNICAL DATA

Form	Powder
Storage Life	12 Months stored between 5°C and 25°C in original containers

Specification writers: These values are not intended for use in preparing specifications. Please contact your local **Geocel® Sales Representative** prior to writing specifications on this product.

SURFACE PREPARATION

All surfaces must be sound and free from all traces of loose material, laitance, oil, dirt and grease. Porous surfaces should be pre-wetted, particularly in hot weather. Avoid ponding water.

APPLICATION

Mix 1kg with approximately ¼ Litre of water. Mix quickly and use straight away.

Keep repair damp for 24 hours after setting by covering it with a damp cloth or newspaper.

For wide cracks mix 1 part **Geocem Fast Set Cement** to 3 parts clean dry sharp sand.

COVERAGE

Approximately 1.5 litre yield per 3kg pack.

CLEANING

Clean all equipment with water immediately after use.

PACKAGING

Geocem Fast Set Cement is available in 3kg tubs.

LIMITATIONS

For thicker applications, crosshatch surface and leave for 2 hours before application of a second layer. Maximum thickness in a single layer is 50mm.

HEALTH AND SAFETY

Geocem Fast Set Cement is irritant wear suitable protective clothing. Avoid contact with skin and eyes. For further information please refer to Health and Safety data sheets available on request.

TECHNICAL SERVICE

For further technical information, advice on suitability for specific applications, or detailed Health and Safety information, contact **Geocel® Technical Service**.

IMPORTANT NOTE The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that Geocel's products are safe, effective and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent.

Geocel's sole warranty is that the product will meet the Geocel sales specifications in effect at the time of shipment.

Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

Geocel specifically disclaims any other express or implied warranty of fitness for a particular purpose or merchantability.

Geocel disclaims liability for any incidental or consequential damages.

Geocel®

Geocel Limited

Western Wood Way, Language Science Park, Plympton, Plymouth, Devon, PL7 5BG

Tel: 01752 334350 Fax: 01752 202065 Email: info@geocel.co.uk

www.geocel.co.uk