

tesa® 64621 Industry

Double-sided transparent self-adhesive tape

PRODUCT INFORMATION

Product Description

tesa® 64621 is a transparent double-sided self-adhesive tape consisting of a PP-carrier and a synthetic rubber adhesive mass system (hotmelt).

With the hotmelt adhesive, tesa® 64621 is solvent free and offers a very high tack.

tesa® 64621 is protected by a siliconized paper liner.

Main Application

- · General purpose fixing tape
- · Self-adhesive mounting of decorative and packaging materials
- Bonding of foils, fabrics, paper and plastic materials

Technical Data

Backing material	PP film	Type of liner	glassine
Colour	transparent	Colour of liner	brown
Total thickness	90 μm	Thickness of liner	70 µm
Type of adhesive	synthetic rubber	Weight of liner	78 g/m ²

Adhesion to

PE (initial) 5.0	N/cm	PE (after 14 days)	6.5 N/cm
_ (''		(, -)	13.0 N/cm 13.5 N/cm

Properties

Temperature resistance short term	80 °C	Humidity resistance	+
Temperature resistance long term	40 °C	Static shear resistance at 23°C	0
Tack	+	Static shear resistance at 40°C	-
Ageing resistance (UV)	0	Fogging	++

Evaluation across relevant tesa® assortment: ++ very good, + good, o medium, - low

For latest information on this product please visit http://l.tesa.com/?ip=64621

Page 1 of 1 / As of 08/08/14

tesa SE

Quickbornstraße 24 20253 Hamburg

Charlotte, N.C. 28209 United States of America

tesa tape inc.

tesa tape Asia Pacific Pte. Ltd.

9 North Buona Vista Drive #04-01 The Metropolis Tower 1 | United States of America | Germany | Phone: +49 (40) 4909 101 | Phone: +1 (704) 554 0707 | Tel: +65 6697 9888 | Fax: +1 (704) 553 5634 | Fax: +65 6659 6390 | Http://www.tesa-asia http://www.tesatape.com http://www.tesa-asia.com

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.