

Datasheet

AT79 High Performance Polythene Self-Amalgamating Tape

RS Stock No: 0494461



General Description

A non-adhesive, polythene self-amalgamating tape with an easily Removed interleave.

- Strong
- Elastic
- Water resistant
- Ozone resistant
- Easily applied
- Resistant to a wide range of chemicals including alkalis, hydraulic fluids and vegetable oils
- High dielectric strength

NOTE

Except where indicated otherwise, the figures stated are average values and should not be regarded as MAXIMUM or MINIMUM values for specification purposes. The Company reserves the right to improve products and any change in specification will result in a re-issue of the relevant 'Technical Data Sheet'. Customers should satisfy themselves that the tape is suitable for their requirements whether after such modifications or otherwise. Please check that you have the latest issue of the 'Technical Data Sheet'. All slitting and length tolerances are to British Standards. Before use the customer is advised to consult the Health & Safety Data Sheet produced by the company for this product, which is available on request.

STORAGE

Tapes stored below the minimum recommended temperature will require warming up to that level before use. Up to 24 hours may be required for this to take place.

Technical Details

Typical Values

Thickness	0.75mm
Breaking Load	12.0 N/cm
Elongation	600%
Electrical Strength	34 kV/mm
RoHS Compliant	Yes
Service Temperature	-35 °C to +130 °C
Application Temperature	0 °C to +40 °C
Storage Temperature	+12 °C to +25 °C