

tesa® 4154

Masking tape

PRODUCT INFORMATION

Product Description

tesa® 4154 is a filmic masking tape to be used to mask glass and metal during etching. tesa® 4154 withstands diluted acids and alkalis. To achieve sharp definition of colour edges tesa® 4154 is also used for multi-colour painting purposes.

Main Application

- Galvanising of metal
- Etching of glass and metal
- Masking during multi-colour painting

Technical Data

■ Backing material	PVC film	■ Adhesion to steel	3 N/cm
■ Type of adhesive	Natural Rubber	■ Elongation at break	67 %
■ Total thickness	65 µm	■ Tensile strength	60 N/cm

Properties

■ Easy to remove	yes	■ Printability	+
------------------	-----	----------------	---

Evaluation across relevant tesa® assortment: ++ very good, + good, o medium, - low

tesa UK Ltd.

Yeomans Drive, Blakelands
Milton Keynes, Bucks MK 14 5LS
Phone: +44 (1) 908 211 333
Fax: +44 (1) 908 211 555
ukenquiry@tesa.com

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.