

HFL1200 FINE LINE MASKING TAPE

DESCRIPTION

This flexible temperature resistant fine line masking tape is especially developed for multi-colour paint applications of plastic parts such as bumpers. It is very thin, conforms to the dimensional changes during oven-drying and does not shrink or lift off. Does not leave residues after removal. The flexibility of the backing material allows good conformance to multi-dimensional services.

CARRIER

0.11mm PVC Copolymer

APPLICATIONS

Car

- Multi-colour paint applications
- Plastic parts (bumpers....)

Industry

- Multi-colour paint applications
- Not recommended for outdoor use

TECHNICAL DETAILS

Adhesion to steel	8.5 N/25mm
Tensile Strength	62.5 N/25mm
Elongation	248%
Temperature Resistance	max. 150°C

APPLICATION

Temperature: between +15°C and +30°C. Surface must be clean and free from dust and grease. Pressure sensitive adhesive must be applied with a maximum of pressure in orders to achieve maximum pressure level. The indicated level of performance will be reached after a bonding period of 24 Hours at 23°C.

STORAGE AND SHELF LIFE

Clean and dry in a well ventilated area, preferably at room temperature between 10°C and 30°C. Stored under these conditions shelf life will be minimum of one year.

Unless stated otherwise all values given are average. All of the tapes in our range should be thoroughly tested on the substrates in the particular application they are intended for. Hi-Bond Tapes Ltd. will not be responsible for product failure unless full testing has been completed. The customer has to decide on the tapes suitability for the intended application.