# **TECHNICAL DATA**

Version 17

# **AT160 High Specification** Waterproof Cloth Tape

### **General description**

A polythene extruded matt cloth tape with a waterproof finish coated with an aggressive pressure sensitive adhesive.

- Very strong
- Easy tear and unwind
- Conformable to awkward shapes •
- Water resistant finish
- Good abrasion resistance
- Non-corrosive adhesive
- Can be written on
- Wide colour range

#### Specification

Certification\* to the following standard may be available on request. DEF STAN 81-25/4.

## **Technical Details**

Typical Values

Thickness		0.33mm
Breaking Load		85 N/cm
Elongation		8%
Adhesion Steel		3.5 N/cm
	Self	2.2 N/cm
Moisture Vapour Permeability		35g/m2/24hrs
Water extract PH		6.5 to 7.5
	Chloride Max	0.05% as NaCl
	Sulphate Max	0.25% as Na2SO4
RoHS compliant		Yes
Service Temperature		-50°C to +80°C
Application Temperature		+10°C to +45°C
Storage Temperature Standard charge for certificate:£25.00.		+12°C to +25°C



#### NOTE

Except where indicated otherwise, the figures stated are average values and should not be regarded as MAXIMUM or MINIMUM values for specification purposes. The Company reserves the right to improve products and any change in specification will result in a re-issue of the relevant 'Technical Data Sheet'. Customers should satisfy themselves that the tape is suitable for their requirements whether after such modifications or otherwise. Please check that you have the latest issue of the 'Technical Data Sheet'. All slitting and length tolerances are to British Standards. Before use the customer is advised to consult the Health & Safety Data Sheet produced by the company for this product, which is available on request.

#### STORAGE

Tapes stored below the minimum recommended temperature will require warming up to that level before use. Up to 24 hours may be required for this to take place.



AFERA Association des Fabricants Européens de Rubans Auto-Adhésifs.

Adding more to adhesive tape

Advance Tapes International Limited Westmoreland Avenue Thurmaston Leicester LE4 8PH England

Tel. +44 (0)116 251 0191 Fax. +44 (0)116 265 2046 contact@advancetapes.com



www.advancetapes.com