

Geocel® ecoSEAL

WINDOW GLASS & FRAME

SILICONE SEALANT

Geocel® ecoSEAL Window Glass & Frame Silicone Sealant is a silicone sealant for external sealing around door and window frames and the bedding in of glass and sealing between glass and framework. Excellent adhesion to most common substrates including PVCu, wood, aluminium, glass and polycarbonate.

- High performance silicone
- Excellent adhesion to PVCu
- Available in White, Clear & Brown, 300ml sausages, box quantity 12, 12 nozzles per box

SPECIFICATIONS

Conforms to ISO 11600-F&G-25LM
Manufactured under ISO 9001



TECHNICAL DATA

Storage Life	12 months stored in original containers below 30°C
Colour	White, Brown, Clear
Cure Type:	Neutral
Tack Free Time	30 minutes @ 23°C 50%RH
Working Time	10 minutes @23°C 50%RH
Cure Rate	2mm per 24 hours @23°C 50%RH
Movement Capability	±50%

Specification writers: These values are not intended for use in preparing specifications. Please contact your local **Geocel® Sales Representative** prior to writing specifications on this product.

APPLICATION

To be applied using a Geocel® **ecoSEAL** Sleeve and a Cox Powerflow CARTRIDGE Heavy Duty Skeleton Gun. Surfaces to be sealed should be clean and dry. Tool within 5-10 minutes of application. Sealant application between +5°C to +40°C. Store in dry conditions below 30°C.

PACKAGING

Geocel® **ecoSEAL Window Glass & Frame Silicone Sealant** is supplied in 300ml sausages packed in boxes of 12.

ANCILLARY MATERIALS & EQUIPMENT

Cox **Powerflow CARTRIDGE**

Geocel® **ecoSEAL Sleeve**

Geocel® **ecoSEAL Spare Nozzles**

Geocel® **ecoSEAL Spare Lid**

HEALTH & SAFETY

Health and Safety data sheets available on request.

TECHNICAL SERVICE

For further technical information, advice on suitability for specific applications, or detailed Health and Safety information, contact **Geocel® Technical Service**.

IMPORTANT NOTE The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that Geocel's products are safe, effective and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent.

Geocel's sole warranty is that the product will meet the Geocel sales specifications in effect at the time of shipment.

Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

Geocel specifically disclaims any other express or implied warranty of fitness for a particular purpose or merchantability.

Geocel disclaims liability for any incidental or consequential damage.



Geocel®

Geocel Limited

Western Wood Way, Lantage Science Park, Plympton, Plymouth, Devon, PL7 5BG

Tel: 01752 334350 Fax: 01752 202065

Email: info@geocel.co.uk

www.geocel.co.uk