


Round Pin Socket Outlets



Description

A range of round pin socket design in the Deta Slimline style.

This uniquely shaped range is easy to install, with coloured terminals, clear white terminal markings and is supplied in individual protective bags.

Features

- unique slim profile with curved top and bottom edges
- only one size 4mm screwdriver needed
- clear white markings
- colour coded terminals
- top facing terminal screws
- terminals have large lead-ins
- 25 year guarantee

Range

2A 1g unswitched socket	S1330
5A 1g unswitched socket	S1331
15A 1g unswitched socket	S1332
5A 1g DP swithed socket	S1333
15A 1g DP switched socket	S1334

Technical Specification
voltage rating 250Vac
current Rating see Range table

no user serviceable parts

Back Boxes

minimum recommended depth

	flush	dry lining	surface
	25mm	35mm	25mm
1g	DB162	DB2540	V1221

Standards

• BS 546: 1950

Terminal Capacity

rommar oupdong								
		2.5mm ²	4mm ²	6mm ²	10mm ²			
	2A	2	1	-				
	5A	2	1	1	1			
	15A	4	2	1	1			

DETA

Kingsway House, Laporte Way Luton, Beds LU4 8RJ Tel. +44 1582 544 500 Fax: +44 1582 544 501 Technical Helpline +44 1582 544 548