


PLIOTER earth straps

Strap: tinned bronze
Cap and wire-strainer: electrogalvanized steel
Section: 2,5 to 50 mm²
Specification: conform to norm NF C15-100




- System of double clamping for tubes and cables simultaneously.
- Contact is established by THC flattening of the conductor between 2 layers of strapping.
- Perfect crimping.
- Wide range of conductors per type of earth strap.
- Low inventory, 7 types for a range of conductors between Ø 2,5 to 50 mm² and of tubes between Ø 8 and 88 mm.

EQUIPOTENTIAL CONNECTIONS - CONNECTIONS TO EARTH - CONNECTIONS TO MASS (C.E.M.)



• Earth straps 2,5 to 50 mm²

type	article number	for cable mm ²	for tube Ø mm	length mm	weight g/pce	width mm	thickness mm	
T 11	0619 0007 000	2,5 ... 6	8 ... 28	150	5	6	0,25	20
T 12	0619 0003 000	2,5 ... 10	16 ... 48	190	17	10	0,25	16
T 13	0619 0004 000	2,5 ... 10	16 ... 88	325	20	10	0,25	15
T 2	0619 0001 000	10 ... 16	16 ... 48	190	53	25	0,25	7
T 3	0619 0002 000	10 ... 16	16 ... 88	325	61	25	0,25	6
T 33	0619 0005 000	25 ... 35	16 ... 88	325	61	25	0,25	6
T 50	0619 0006 000	50	16 ... 88	330	100	32	0,25	1

• Tool for earth straps PLIOTER T11 - T12 - T13

type	article number	
T-2000	0619 0050 000	1



For clamping and cutting our earth straps T11, T12 and T13.