

# Hose holder with cover - WP-BASE C PA HF 28,2 BK - 3240962

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Hose holder with cover

Image shows WP-TCC PA HF 10.0 BK version



### Key commercial data

Packing unit	25 pc
Minimum order quantity	25 pc
GTIN	4 046356 710701
Weight per Piece (excluding packing)	9.11 g
Custom tariff number	39174000
Country of origin	Germany
Note	Made to Order (non-returnable)

## Technical data

#### **Dimensions**

Hole diameter	6.5 mm
Diameter	28.5 mm

#### Ambient conditions

Ambient temperature (exerction)	40 °C 44E °C
Ambient temperature (operation)	-40 °C 115 °C

#### General

Color	black
Components	Halogen-free
Inflammability class according to UL 94	V0
Material	PA



# Hose holder with cover - WP-BASE C PA HF 28,2 BK - 3240962

### Classifications

eCl@ss

eCl@ss 4.0	27141131
eCl@ss 4.1	27141131
eCl@ss 5.0	27141131
eCl@ss 5.1	27141120
eCl@ss 6.0	27141120
eCl@ss 7.0	27141120

#### **ETIM**

ETIM 3.0	EC000897
ETIM 4.0	EC000127
ETIM 5.0	EC000127

### **UNSPSC**

UNSPSC 6.01	30211812
UNSPSC 7.0901	39121410
UNSPSC 11	39121411
UNSPSC 12.01	39121411
UNSPSC 13.2	39121411

## Approvals

Approvals

Approvals

UL Recognized

Ex Approvals

Approvals submitted

Approval details

UL Recognized **\$\)** 

Accessories

Accessories

Corrugated pipe



## Hose holder with cover - WP-BASE C PA HF 28,2 BK - 3240962

### Accessories

Protective hose - WP-PA HF 28,5 BK - 3240684



Polyamide protective hose, inflammability class V0, UV resistant, 1 Pcs. / Pkt. = roll à 50 m

Protective hose - WP-PA HF-HB 28,5 BK - 3240842



Polyamide protective hose, inflammability class HB, UV resistant, 1 Pcs. / Pkt. = roll à 50 m

Phoenix Contact 2015 @ - all rights reserved http://www.phoenixcontact.com