


Product Description

High tensile strength; Saving space; Vibration protection; Universally useable



Application range

- In combination with protective conduit
- SILVYN® FPS/FD-PU
- SILVYN® AS/EDU-AS/EMC AS-CU/AS-P
- Mechanical engineering
- Plant engineering and construction

Benefits

- High tensile strength
- Saving space
- Vibration protection
- Universally useable

Design

- PG connection thread
- hexagonal collar
- Inner sleeve (not included in the delivery)
- Sealing element
- Cap nut

Note

- Necessary inner sleeve is not included
- SILVYN® EE-K
- SILVYN® US-AS/US-EDU-AS
- Has to be ordered separately in dependence of the chosen conduit



Product features

- Compact design
- Applicable as an EMC gland by using the brass ring SILVYN® US-MS-DR

Technical Data

Material

Body:Nickel plated brass sealing: TPE

Range of temperature

-40°C up to + 125°C

Degree of protection

IP 40 (with SILVYN® AS, EDU-AS and EMC AS-CU) IP 65 (with SILVYN® FPS and AS-P) IP 66 (with SILVYN® FD-PU)

Article List

Part number	PG size	Overall length C mm	D mm	F mm	SW 1/2 mm	Suitable for SILVYN® FPS/FD-PU	Suitable for SILVYN® AS	Suitable for SILVYN® EDU-AS/AS-P/EMC AS-CU	Pieces / PU
SILVYN® US									
61795080	7	28	7	9.5	15 / 17	7 x 10	8 x 10	7 x 10	50
61795090	9	30	7	11.5	19 / 21	10 x 14	11 x 14	10 x 14	50
61795100	11	30	7	15.5	23 / 25	13 x 17	14 x 17	13 x 17	50
61795110	13.5	30	7	17	25 / 27	15 x 19	16 x 19	15 x 19	50
61795120	16	30	7	19	27 / 29	16 x 21	18 x 21	17 x 21	50
61795130	21	40	10	24	34 / 36	22 x 27	23 x 27	22 x 27	25
61795140	29	40	10	32.5	43 / 45	29 x 36	31 x 36	29 x 36	25
61795150	36	40	10	42	52 / 54	38 x 45	40 x 45	38 x 45	20



61795170	48	45	10	55	63 / 77	48 x 56	51 x 56	49 x 56	10
----------	----	----	----	----	------------	---------	---------	---------	----