

Fittings



TYPE A IP66, IP67
& IP68 2 bar 30 minutes with SWM

STRAIGHT FITTING – FIXED EXTERNAL THREAD
For insertion into knockouts using a locknut.
Black only. Grey made to order.



TYPE C90 IP66, IP67
& IP68 2 bar 30 minutes

90° ELBOW FITTING – FIXED EXTERNAL THREAD
For insertion into knockouts using a locknut.
Black only. Grey made to order.



TYPE FL90 IP66, IP67
& IP68 2 bar 30 minutes

90° ELBOW FITTING – PANEL MOUNT FLANGE
For panel mounting via 4 hole fixing
& integral face seal.



NOMINAL CONDUIT SIZE	CONDUIT PITCH	METRIC THREAD	PART NUMBER*	PG THREAD	PART NUMBER	METRIC THREAD	PART NUMBER*	PG THREAD	PART NUMBER	PART NUMBER
10	FINE	M16	ASF10/M16/A	PG9	ASF10/PG9/A	M16	ASF10/M16/C90	PG9	ASF10/PG9/C90	–
13	FINE	M16	ASF13/M16/A	PG9	ASF13/PG9/A	M16	ASF13/M16/C90	PG9	ASF13/PG9/C90	–
16	FINE	M16	ASF16/M16/A	PG11	ASF16/PG11/A	M16	ASF16/M16/C90	PG11	ASF16/PG11/C90	–
16	FINE	M20	ASF16/M20/A	PG13.5	ASF16/PG13/A	M20	ASF16/M20/C90	PG13.5	ASF16/PG13/C90	–
21	FINE	M20	ASF21/M20/A	PG16	ASF21/PG16/A	M20	ASF21/M20/C90	PG16	ASF21/PG16/C90	–
21	COARSE	M20	ASC21/M20/A	PG16	ASC21/PG16/A	M20	ASC21/M20/C90	PG16	ASC21/PG16/C90	–
28	FINE	M25	ASF28/M25/A	PG21	ASF28/PG21/A	M25	ASF28/M25/C90	PG21	ASF28/PG21/C90	–
28	COARSE	M25	ASC28/M25/A	PG21	ASC28/PG21/A	M25	ASC28/M25/C90	PG21	ASC28/PG21/C90	–
34	FINE	M32	ASF34/M32/A	PG29	ASF34/PG29/A	M32	ASF34/M32/C90	PG29	ASF34/PG29/C90	ASF34/FL/90
34	COARSE	M32	ASC34/M32/A	PG29	ASC34/PG29/A	M32	ASC34/M32/C90	PG29	ASC34/PG29/C90	ASC34/FL/90
42	COARSE	M40	ASC42/M40/A	PG36	ASC42/PG36/A	M40	ASC42/M40/C90	PG36	ASC42/PG36/C90	ASC42/FL/90
54	COARSE	M50	ASC54/M50/A	PG48	ASC54/PG48/A	M50	ASC54/M50/C90	PG48	ASC54/PG48/C90	ASC54/FL/90

**Supplied with locknut.

To order complete Part No, add colour - e.g. ASF21/M20/A/BL

ADAPTASEAL[®]
SYSTEM
FROM ADAPTAFLEX

Adaptaseal compression fittings are widely used with Type PA/PR/PI conduits, e.g. in external applications requiring assured IP66, IP67 or IP68 weatherproofing, flexibility and high mechanical strength.

In addition, Adaptaseal fittings complement LFH Type PA & PR conduits for assured fire performance where public safety or the integrity of electronic equipment are of concern.



Approvals may be limited to certain products, see approvals on page 44.

Accessories

TYPE T IP66 & IP67

INSPECTION T-PIECE

For connection to corrugated flexible conduit.
Black only.



TYPE RK IP67

REDUCING KIT

For connection to a reduced conduit size.
Black only.



TYPE AWB

ANTI-VIBRATION WASHER

Acetal washer prevents fitting loosening under vibration.



FOR CONNECTION TO NOMINAL CONDUIT SIZE	PART NUMBER	REDUCING TO CONDUIT SIZE 10	REDUCING TO CONDUIT SIZE 13	REDUCING TO CONDUIT SIZE 16	REDUCING TO CONDUIT SIZE 21	REDUCING TO CONDUIT SIZE 28	PART NUMBER
10	ASF10X3/T	-	-	-	-	-	AWB13
13	ASF13X3/T	RK13-10	-	-	-	-	AWB13
16	ASF16X3/T	RK16-10	RK16-13	-	-	-	AWB16
21	ASF21X3/T	RK21-10	RK21-13	RK21-16	-	-	AWB21
21	ASC21X3/T	RK21-10	RK21-13	RK21-16	-	-	AWB21
28	ASF28X3/T	-	RK28-13	RK28-16	RK28-21	-	AWB28
28	ASC28X3/T	-	RK28-13	RK28-16	RK28-21	-	AWB28
34	ASF34X3/T	-	-	-	RK34-21	RK34-28	AWB34
34	ASC34X3/T	-	-	-	RK34-21	RK34-28	AWB34
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-

- See pages 38 - 45 for Technical Details
- See page 23 for Accessories

