

Xpelair Commercial Sensors and Switches



Single Fan Controller FR22/30

Ref. 21868AW

- Sliding switches
- On/Off
- 2 speeds: low- high speed
- Extract - intake airflow
- Power 'on' indicator
- For surface or recess mounting
- Supply voltage: 220 -240V 50Hz
- Gloss white
- Use with: GX9, GX12, WX9, WX12, PX9, PX12, RX9, RX12
- w210 x h86 x d41mm



Single Direction Group Fan Controller XCC1

Ref. 21859AW

- Sliding switches and speed control knob
- On/Off
- Infinitely variable speed control
- Single direction: extract or intake selected at installation
- Power 'on' indicator
- For surface or recess mounting
- Supply voltage: 220 - 240V 50Hz
- Gloss White
- Use with: GX9, GX12, WX9, WX12, PX9, PX12, RX9, RX12

Note: do not mix fan size. For use with up to 4 - size 12 or 6 - size 9 fans units.

- w160 x h86 x d45mm



Reversible Group Fan Electronic Controller EC6H

Ref. 21854AW

- Sliding switches and speed control knob
- On/Off
- Infinitely variable speed control
- Extract - intake airflow
- Power 'on' indicator
- For surface or recess mounting
- Supply voltage: 220 - 240V 50Hz
- Gloss White
- Use with: GX9, GX12, WX9, WX12, PX9, PX12, RX9, RX12

Note: do not mix fan size. For use with up to 4 - size 12 or 6 - size 9 fans units.


- w160 x h86 x d45mm



Remote Humidistat XRH

Ref. 21856AW

- Stand alone humidistat switches on when RH rises to preset level and Off when it declines
- Fan operation indicator light
- Pullcord operated override switch
- Surface or recess mounting
- White finish
- Supply voltage 220 - 240V 50Hz
- Use with: GX6, GX9, GX12, WX6, WX9, WX12, PX6, PX9, PX12, RX6, RX9 & RX12
- w160 x h86 x d41mm



Passive Infrared Sensor XPIRA

Ref. 21871AA

- Position to switch the fan on when body movement is detected. Ideal for infrequently used public spaces
- Built in run on timer to avoid nuisance tripping
- For indoor use only
- Use with: GX6, GX9, GX12, WX6, WX9, WX12, PX6, PX9, PX12, RX6, RX9 & RX12
- w86 x h86mm



Time Controller DT20B

Ref. 21850AW

- Usually connected to the lighting circuit. Fan switches On with the light. Provides continued ventilation run-on period after the light has been switched off
- User adjustable up to 20min
- Surface or recess mounting
- White finish
- Supply voltage 220-240V 50Hz
- Use with: GX6, GX9, GX12, WX6, WX9, WX12, PX6, PX9, PX12, RX6, RX9 & RX12
- w100 x h86 x d45mm



Controller HC301

Ref. 21877AW

- On/Off switch
- Fan only/fan and heater options
- Variable thermostatic control
- Suitable for surface or recessed installation
- Colour: White
- Used with WH30 and WHP30
- w210 x h86 x d41mm



Air Quality Sensor AQS

Ref. 92097AW

- Provides fully automatic control
- Detects contaminants such as cigarette smoke, body odours, toilet odours and cooking smells
- Activates ventilation system when preset threshold level is exceeded
- Can control up to six fans and accessories
- Integral timer adjustable from 3 - 30 mins
- LED status indicator
- Surface or recess mounting
- Supply voltage 220-240V 50Hz
- w160 x h86 x d41mm