





The company named below has been authorized by Canadian Standards Association to represent the products listed in this record as "CSA Certified" or "CSA Accepted", as applicable, and to affix the CSA Mark to these products according to the terms and conditions of the CSA Service Agreement and applicable CSA program requirements (including additional Markings).

NUMBR 043279W0000 February 9, 1995 (Replaces: March 4, 1994)

CLASS 4823 04 (Re-examination Service)

ELMWOOD SENSORS INC.  
 Sub. of Fasco Industries Inc.  
 500 Narragansett Pk. Dr.  
 Pawtucket, RI 02861-4325

43279

TEMPERATURE-INDICATING AND REGULATING EQUIPMENT - Thermal Cut-offs

THE FOLLOWING MEET THE REQUIREMENTS OF CSA STD. C22.2 NO 209-M1985 and E.C.N. 485:

- Single operation thermostat, 3/4 in, Type 2541, rated 240/277/480V ac, 40/22/13A (non-ind); 120/240/277V ac, 16/12/8 FLA, 84/72/42 LRA, 670/670/770VA pd; 12/48V dc, 30/12A (non-ind) max. Functioning temp Tf 350F, non-resettable above -35C.
- Single operation thermostat, 1/2 in, Type S35 with prefixes 2450, 3450, 2455, 3455, 2450R, 3450R, 2455R, 3455R with or without prefix letters C, G, H, K or M, Type S26 with prefixes 2450R, 2455R, 2455RC, 2456R, 2450, 2455, 3450, 3455, 3450R, 3455R with or without Prefix C, G, H or K and 2458RC, 2459RC; rated 120/250/277V ac, 15/12.5/10A (non-ind); 120/240V ac, 5.8/2.9 FLA, 34.8/17.4 LRA, 125/160VA pd; 240V ac, 0.5A; 12/50V dc, 12.5/0.5A. Functioning temp Tf 350F, on types with suffix "C" Tf 600F, non-resettable above -35C.
- Single operating thermostat Types 2450C, 3450C, 2450CH and 3450CH, with Suffix S45, rated 120/250V ac, 10/5A, max calibrated temperature 260C (500F), non-resettable (automatically) above -35 Deg C.
- Non-renewable thermal cutoffs, MTP Series, Part No WAXXX, 120V ac, 5A (non-ind), 1 FLA, 6 LRA:

Part No in XXX position	Tf(C)	Th(c)	Tm(C)
072	72	65	160
077	77	67	160
084	84	76	160
093	92	85	160
098	97	93	160
109	109	103	160
117	116	110	160
128	128	119	160
141	140	134	160
152	152	144	160

(Cont'd)