


Connection Units



Description

This stylish range is easy to install, with coloured terminals, clear white terminal markings and the frontplates are supplied in protective bags.

Features

- supplied with back box
- concave rockers
- only one size 4mm screw driver needed
- clear white terminal markings
- colour coded terminals
- terminals have large tapered lead-ins
- captive and backed out terminals
- front plate comes in protective bag
- neon versions available
- neon leads enclosed
- fuse carrier can be locked in the out position
- 2 earth terminals
- 25 year guarantee

Range

13A fused unswitched	M1210
13A fused unswitched flex outlet	M1210FL
13A fused switched DP	M1211
13A fused switched DP flex outlet	M1211FL
13A fused switched DP neon	M1212
13A fused switched DP neon & flex outlet	M1212FL

Technical Specification

voltage rating	250Vac
current rating	13A
contact gap	3mm
size	78mm x 78mm
depth	46mm

no user serviceable parts

Standards

- BS 1363 Part 4 : 1995
- Fuse – BS 1362

Back Boxes

	knockouts	
	sides	back
1g	5	1

- all knockouts are 20mm dia.

Terminal Capacity

	2.5mm ²	4mm ²	6mm ²	10mm ²
L & N	4	3	2	1

DETA

Kingsway House, Laporte Way
Luton, Beds LU4 8RJ UK
Tel. +44 1582 544 500 Fax: +44 1582 544 501
Technical Helpline +44 1582 544 548