

technical hotline +44 (0)1268 563720

boxes and ancillary products | wiring devices

Steel Boxes

ARCHITRAVE FLUSH

DUAL FLUSH

Metal Frames For Panel Mounting

PVC Boxes

19mm SURFACE

32mm SURFACE













3921ZIC 1 GANG

10

887ZIC DUAL BOX

DIVIDING SCREEN

FOR DUAL BOX

888ZIC

K2200 1 GANG

K2202

2 GANG

5

10

5

3 GANG

10

2120WHI FOR 1, 2 AND **PLATESWITCHES** 10

2180WHI 1 GANG

2181WHI 1 GANG

2182WHI 2 GANG

10

10

2183WHI 2 GANG

5

5

DIMENSIONS: 1 gang: 75 x 27 x 27mm FIXING CENTRES: 1 gang: 60.3mm KNOCKOUTS:

1 gang: 3 x 16mm

BS 4662: 2006

Dual box 887ZIC will accept any two flush accessories with 86mm square plates and two M3.5 fixing holes on 60.3mm centres.

75 x 161 x 35mm KNOCKOUTS: 2 gang 10 x 20mm 4 x 25mm

BS 4662: 2006

DIMENSIONS:

FIXING CENTRES: 1 gang: 60.3mm 2 gang: 120.6mm BS 5733: 2010

With earth terminal DIMENSIONS:87 x 87mm FIXING CENTRES: 60.3mm

KNOCKOUTS 'Cut-out' provided in top and bottom for 16mm oval PVC conduit. 20mm round 'pushout' type knockout in base for cable entry. Fixing holes are also provided for mounting to wall or over BS 4568 Pt.2 small circular boxes, BS 5733; 2010

DIMENSIONS: 87 x 87mm FIXING CENTRES: 60.3mm KNOCKOUTS:

2180: One 'push-out' for 20mm oval conduit in top, one 'cut-out' for 20mm or 25mm oval conduit and one 20mm round 'push-out' in the base.

2181: One 'push-out' for 20mm round conduit in top and one 20mm round 'push-out' in base. BS 5733: 2010

DIMENSIONS: 87 x 148mm FIXING CENTRES: 120.6mm KNOCKOUTS: 2182: Two 'push-outs' for

20mm oval conduit in top, two 'cut-outs' for 20mm or 25mm oval conduit and one 20mm round 'push-out' in base 2183: One 'push-out' for 20mm round conduit in top and one 20mm round 'push-out' in base. BS 5733: 2010

Blank **Plates**

METALCLAD PLUS

METALCLAD

PVC Boxes

32mm SURFACE Guardian Socket Cover

Moulded Boxes DRY LINING 35mm FLUSH





10


10

5





1



QFB1WHI

QFB2WHI

1 GANG

2 GANG

20

10

K3390ALM FOR 1 GANG SURFACE BOXES K899 & K829

K3369ALM FOR 2 GANG SURFACE BOXES K830 & K897

DIMENSIONS: K3390: 86 x 86mm K3369: 86 x 147mm

FIXING CENTRES: K3390: 60.3mm K3369: 120.6mm BS 5733: 2010

5 3390ALM FOR 1 GANG SURFACE BOXES 899 & 829

> 3370ALM FOR 1 GANG SURFACE BOXES 891 & 821

3369ALM FOR 2 GANG SURFACE BOXES 892 & 822

DIMENSIONS: 3390: 81 x 81mm 3370: 76 x 76mm 3369: 76 x 136mm

FIXING CENTRES: gang: 60.3mm 2 gang: 120.6mm BS 5733: 2010

10 K2181WHI

FOR 1 GANG LOGIC PLUS™ POWER ACCESSORIES

5 K2183WHI FOR 2 GANG LOGIC PLUS™ POWER ACCESSORIES

5 K2185WHI FOR 3 GANG LOGIC PLUS™ POWER ACCESSORIES

KNOCKOUTS: K2181: One 'cut-out' for 20mm round conduit in top face, one 'cut-out' for 20mm or 25mm oval conduit in lower face and one 20mm round 'push-out' in the base.

K2183 and K2185: One 'cut-out' for 20mm round conduit in top face, two 'cut-outs' for 20mm or 25mm oval conduit in lower face and one 20mm round 'pushout in the base. Both boxes are suitable for fitting over 1 gang and 2 gang BS 4662 flush steel boxes respectively

DIMENSIONS: gang: 87 x 87mm 2 gang: 87 x 148mm 3 gang: 87 x 208mm

FIXING CENTRES: gang: 60.3mm gang: 120.6mm 3 gang: 180.9mm BS 4662: 2006

where applicable

Accessories not supplied with unit. FIXING CENTRES: 60.3mm

GWR1WHI

1 GANG

All round flange for a flush fit. One piece moulded lug automatically snaps into place. No rear projections. Clamp device on cable entry. Will accommodate partition thickness between 6mm and 16mm. Earth terminal facility. BS 4662: 2006

MOUNTING BOX ACCESSORIES see page 201

5