

# Thermomagnetic device circuit breaker - TMCP 3 M1 300 3,0A - 0916505

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Thermomagnetic circuit breaker, 3-pos., normal blow, 1 N/O contact and 1 N/C contact

The illustration shows version TMCP 1 F1 300 2,0A



## Key commercial data

Packing unit	2 pc
GTIN	 4 017918 601393
Weight per Piece (excluding packing)	165.9 g
Custom tariff number	85362010
Country of origin	Germany
Note	Made to Order (non-returnable)

## Technical data

### General

Mounting type	On base element
Color	black
Number of positions	3
Surge voltage category	II
Insulating material	PA66
Inflammability class according to UL 94	V-2

### Electrical data

Fuse type	Automatic device
Rated surge voltage	2.5 kV
Rated voltage	250 V AC
	65 V DC
Rated current I <sub>N</sub>	3 A
Insulation resistance R <sub>iso</sub>	> 100 MΩ (500 V DC)
Rated short-circuit switching capacity I <sub>cn</sub>	400 A

# Thermomagnetic device circuit breaker - TMCP 3 M1 300 3,0A - 0916505

## Technical data

### Electrical data

	2500 A (32 V DC)
Short-circuit switching capacity $I_k$	5000 A UL 1077: 277 V AC/480 V AC
	2000 A UL 1077: 65 V DC
Dielectric strength	3000 V AC (Actuation area)
	1500 V AC (Main to auxiliary circuit)
	1000 V AC (Auxiliary circuit 11 - 12 to 23 - 24)
Cycles, max.	10000 (At 1 x $I_n$ , inductive)
Pollution degree	2
Surge voltage category	II
Insulating material group	II

### Dimensions

Height	50 mm
Width	37.5 mm
Depth	78.5 mm
Complete module height	115 mm
Complete module width	38 mm
Complete module depth	121 mm

### Ambient conditions

Degree of protection	IP30 (Actuation area)
	IP00 (Connection area)
Ambient temperature (operation)	-30 °C ... 60 °C

### Connection data

Connection method	pluggable
-------------------	-----------

### Standards and Regulations

Standards/specifications	EN 60934
	UL 1077

## Classifications

### eCl@ss

eCl@ss 4.0	27141116
eCl@ss 4.1	27141116
eCl@ss 5.0	27141116
eCl@ss 5.1	27141116
eCl@ss 6.0	27141116
eCl@ss 7.0	27141116
eCl@ss 8.0	27141116

# Thermomagnetic device circuit breaker - TMCP 3 M1 300 3,0A - 0916505

## Classifications

### ETIM

ETIM 2.0	EC000899
ETIM 3.0	EC000899
ETIM 4.0	EC000899
ETIM 5.0	EC000899

### UNSPSC

UNSPSC 6.01	30211812
UNSPSC 7.0901	39121411
UNSPSC 11	39121411
UNSPSC 12.01	39121411
UNSPSC 13.2	39121411

## Approvals

### Approvals

---

#### Approvals

CSA / UL Recognized / EAC

---



#### Ex Approvals

---

#### Approvals submitted

---

## Approval details



## Accessories

### Additional products

## Thermomagnetic device circuit breaker - TMCP 3 M1 300 3,0A - 0916505

### Accessories

Box mounting base - TMCP SOCKET M - 0916589



Modular socket element, 2-position, for holding two circuit breakers, each with a single position

---

End cover - TMCP CONNECT LR - 0916592



End cover, Length: 115 mm, Width: 6 mm, Color: black

---

---