


# **25A Connection Plates**



#### Description

This uniquely shaped, easy to install, range is designed to match the Deta Slimline range of accessories. With coloured terminals, each product is supplied in individual protective bags.

#### **Features**

- unique slim profile with curved top and bottom edges
- only one size 4mm screwdriver needed
- colour coded terminals
- dual terminals of live, neutral and earth
- large terminal capacity
- 25 year guarantee

## Range

1g blank connection plate	S1200
2g blank connection plate	S1201
25A connection plate with flex	S1215
outlet	
25A connection plate, no flex	S1216
outlet	
45A cooker cable outlet	S1217

Technical Specification Voltage rating 250Vac Current Rating 25A

No user serviceable parts

#### **Back Boxes**

minimum recommended depth

			_		
	flush	dry lining	surface		
	25mm	35mm	25mm		
1g	DB162	DB2540	V1221		
	47mm	46mm	46mm		
S1217	DB167	DB2542	V1228		

### Standards

• BS 5733

#### **Terminal Capacity**

	2.5mm²	4mm <sup>2</sup>	6mm <sup>2</sup>	10mm <sup>2</sup>
L&N	5	3	2	1

#### DETA

Kingsway House, Laporte Way Luton, Beds LU4 8RJ Tel. +44 1582 544 500 Fax: +44 1582 544 501 Technical Helpline +44 1582 544 548