



## Heat Shrinkable Tubing 3:1 in a Kit

### Shrinkit 321-A Basic - with adhesive liner

The black tubing is mainly used for environmental sealing of splices and connectors. The transparent tubing is typically used for protection of cable markers.

#### Features and Benefits

- Adhesive lined heat shrink tubing
- Attractive and reusable kit ideal for assembling and identification
- Inner wall melts when heated and is forced into gaps
- Adhesive forms seal against moisture as tubing cools
- Black tubes mainly for the protection of connectors and splices
- Clear tubing ideal for protection of printed label markers
- Case can be re-used for storing nails, screws, nuts, fish hooks, etc.



Shrinkit 321-A Basic.

<b>MATERIAL</b>	Polyolefin, cross-linked (PO-X)
<b>Shrink Ratio</b>	3:1
<b>Operating Temperature</b>	-55 °C to +110 °C
<b>Minimum Shrink Temperature</b>	+110 °C
<b>Longitudinal change after shrinkage</b>	+1 %/-15 % max.
<b>Dielectric Strength</b>	15 kV/mm according to ASTM D2671
<b>Flammability</b>	self-extinguishing (except for transparent)
<b>Insulation Class</b>	A (VDE 0530)
<b>Specifications</b>	SAE - AMS - DTL-23053/4 Class 3 (except clear)



Heat Shrinkable Tubing 3:1 with adhesive



COMP.	Supplied Ø D min.	Recov. Ø d max.	Length (L)	Wall (WT)	Colour	Content (pcs.)	Article-No.
1	3.0	1.0	35.0	1.00	Black (BK)	25	380-03004
2	12.0	4.0	35.0	1.70	Black (BK)	10	
3	3.0	1.0	35.0	1.00	Transparent (CL)	25	
4	6.0	2.0	35.0	1.10	Black (BK)	15	
5	6.0	2.0	35.0	1.10	Transparent (CL)	15	
6	6.0	2.0	35.0	1.10	Transparent (CL)	15	
7	6.0	2.0	35.0	1.10	Black (BK)	15	
8	12.0	4.0	80.0	1.70	Black (BK)	5	
	12.0	4.0	80.0	1.70	Transparent (CL)	5	

All dimensions in mm. Subject to technical changes.



For product specific approvals and specifications please refer to the Appendix.