## 95 26 165 Cable Shears with opening spring





## £ 1000 V @ 🚭 🔁 📲 MM

- for cutting copper and aluminium single conductors as well as multiple stranded cables
- not suitable for steel wire and hard drawn copper conductors
- precision ground, hardened blades
- clean and smooth cut without crushing and deformation
- easy cutting with one-hand operation
- guard prevents operators' fingers being pinched

Cut performed with a

clean cut without any

Cable Shear: easy,

deformation of the

- adjustable bolted joint, self-retaining screw
- High-grade special tool steel, forged, oil-hardened • Style:internal opening spring, protected and captive

Article No.	95 26 165	
EAN	4003773069980	
ТооІ	chrome plated	
Handles	insulated with multi-component grips, VDE-tested	
Style	2	C
Insulation standard	IEC 60900 DIN EN 60900	ef
Cutting capacity copper cable, multiple-stranded (diameter) Ø mm	15	in co ar ca
Cutting capacity copper cable, multiple-stranded mm <sup>2</sup>	50	
AWG	1/0	
Length mm	165	
Net weight g	275	

Cut performed with a Diagonal Cutter: high effort required, inaccurate cut, considerable deforming and crushing of the cable



cable

95 26 165: with internal opening spring

technical change and errors excepted

