



### oil gun, HHÖP

with ZBH, connection M 10 x 1

**Item number:** 12 602  
**EAN:** 4103810126024  
**Discount group:** A

#### technical data

oil gun connection, pressure side,  
with metal adapter: M 10 x 1  
capacity: 500 ml  
loading: utilising a sealing cap  
diameter oil plunger: 9  
actuation oil plunger: manual with lever  
delivery rate / stroke: proportional to the manual lever operating distance,  
max. 1,4 cm<sup>3</sup>  
discharge pressure (bar): up to 400  
burst pressure (system): 850 bar  
burst pressure (oil gun head): 1200 bar  
wall thickness pipe: 1,0  
colour: silver  
package: polybag, blank, with Bar code  
dimensions packaging LxWxH  
(mm): 340 x 125 x 70  
weight including package (kg): 1,2

#### specification

- With 1 spout, angled, M 10 x 1, 150 mm
- With 1 coupler, 4 jaws, M 10 x 1, with ball valve

#### notes

- with double plunger with leak-proof construction for oils and liquid greases
- Chain retrieval of two-way plunger
- pump piston with high accuracy of fit to the cylinder
- No dummy (apparent) lubrication. Sealing system: O-ring and ball valve prevent oil compressed in the oil gun head from feeding back.
- Performance unchanged after 5000 actuating cycles
- Oil gun head and sealing cap, zinc die casting Z 410
- Slip-proof handle on the lever of the lever oil gun
- Allows lubrication in difficult to reach locations because the smallest lever operation results in oil being pumped reliably to the lubrication point.
- Enables even under extreme backpressure, a variable lubrication pressure with steady effort applied

#### packaging

dimensions LWH (mm): 400 x 360 x 145  
Weight (kg): 12,7  
Packing unit: 10.0