

Feet

XCFF 88×260	<p>Feet Including fastener kit Aluminium, die-cast</p> <p>Foot for beam XCBM/ XCBL ..×88 Max. bending moment 1500 Nm</p>	
XCFF 64×210	<p>Foot for beam XCBM/ XCBL ..×64 Max. bending moment 750 Nm</p>	
XCFF 44×130	<p>Foot for beam XCBM/ XCBL ..×44 Max. bending moment 250 Nm</p>	
XCFB 88 F	<p>Foot plate for beam XCBM/XCBL ..×88 Aluminium, anodized Mounting: MF6S 8×30 (4) or MF6S 6×30 (4) Max. bending moment 200 Nm</p>	
XCFB 44 F	<p>Foot plate for beam XCBM/XCBL ..×44 Aluminium, anodized Mounting: MF6S 8×30 (1) or MF6S 6×30 (4) Max. bending moment 50 Nm</p>	
XCFS 12×68	<p>Adjusting foot Including nut Steel, electro-zinc-plated</p> <p>M12 thread Mounting: XCFE .. M12 Max. vertical load 2500 N</p>	
XLFS 8	<p>M8 thread Max. vertical load 400 N</p>	
XCAG 80 A XCAG 80 BA	<p>Guide rollers Including fastener kit Steel, electro-zinc-plated Mounting: XCAN 8 or XCFE .. M12 Max. vertical load 600 N</p> <p>Guide roller Guide roller with multistop brake</p>	