
LD · LDN SERIES

Technical data

Operating temperature -10°C ~ +60°C

LD · LDN SNAP-IN BATTERY BOX






FEATURE

- Can be installed to panel thickness 1.0 3.0mm.
- Built-in 2 × M3 screw holes for sure installation.





AA Battery type



006P Battery type




Components

Ref. #	Part name	Pcs	Material / Size	Color / Finish
1	Battery box	1	ABS (UL94HB) / PC+ABS (UL94V-0)	Ivory · Black, White
2	Cover	1	ABS (UL94HB) / PC+ABS (UL94V-0)	Ivory · Black, White
3	Battery contact	3~5	Brass + Steel spring	Nickel plated
4	Lead wire (LDN only)	2	PVC + Copper wire / L=140	Black · Red
5	Battery snap (006P only)	1	PVC / ABS + Copper wire / L=150	Black + Red · Black wire


LD · LDN dimensions

• CAD data is downloadable from our website.


LD · LDN-006P




LD · LDN-2



LD · LDN-3



LD · LDN-4



Color & Material

Color code	Color	Material		
Α	Ivory	ABS (UL94HB)		
В	Black	ABS (UL94HB)		
W	White	PC+ABS (UL94V-0)		

Part no. / Components


Please suffix color code at the end of part number


□ when ordering LD series.

	. Todos samin solo: sodo de mo sila el pare nambo. El mien el delinig Eb solice.					
Part no.	Battery compartments	Lead wire / Battery snap	Weight(g)			
LD-006P□	9V battery × 1	Battery snap (PVC housing)	24			
LD-2□	AA×2	Without	24			
LD-3□	AA × 3	Without	26			
LD−4□	AA×4	Without	35			
LDN-006P□	9V battery × 1	Battery snap (ABS housing)	24			
LDN-2□	AA×2	With lead wire L=140mm	24			
LDN-3□	AA × 3	With lead wire L=140mm	26			
LDN-4 □ AA × 4		With lead wire L=140mm	35			



LD · LDN Mounting hole dimensions





Mount hole dimensions

Part no.	W₁ (thickness=1.0mm)	W ₂ (thickness=2.0~2.5mm)	W ₃ (thickness=3.0mm)	D1	n	х
LD / LDN-2 · 006P□	36.5	38.5	40.5	70.6	40.5	34
LD / LDN-3□	51	52.5	54	70.4	53	48.5
LD / LDN-4□	66.5	68.5	70.5	70.6	70.1	64

 $\bullet~W_{_1}$ / $W_{_2}$ / $W_{_3}$ dimension depending on the thickness.



