


19615

Sliding block, sliding block profile, spring



- ▶ Sliding block for reliable absorption of high forces
- ▶ Sliding block profile for self-assembly of individual fastening elements
- ▶ Profile finishing: not required

Technical data (p. 19-5)




00110897

Slot	
6 (M5)	3000 N
8 (M8)	6000 N
10 (M8)	8000 to 18,000 N ¹⁾

¹⁾ Depending on profile (p. 19-5)

Sliding block	Slot	M	h (mm)	l (mm)	ESD		No.	
Steel, galvanized	6	M4	4.0	12		100	3 842 542 692	
		M5	4.0	12		100	3 842 542 693	
	8	M4	6.0	16		100	3 842 514 928	
		M5	6.0	16		100	3 842 514 929	
		M6	6.0	16		100	3 842 514 930	
		M8	6.0	16		100	3 842 514 931	
	10	M5	10.5	20		100	3 842 528 741	
		M6	10.5	20		100	3 842 528 738	
		M8	10.5	20		100	3 842 528 735	
	Steel, stainless	6	M4	10.5	20		100	3 842 523 140
			M5	10.5	20		100	3 842 523 142




00110898

Slot	
6 (M5)	3000 N
8 (M8)	6000 N
10 (M8)	8000 to 18,000 N ¹⁾

¹⁾ Depending on profile (p. 19-5)

Sliding block profile	Slot	h (mm)	l (mm)	No.
Steel, galvanized	6	4.0	1000	3 842 542 694
Steel, stainless	6	4.0	1000	3 842 523 438
Steel, bare, oiled	8	6.0	1000	3 842 510 078
	10	10.5	1000	3 842 528 744



19864

- ▶ The spring assists with the assembly and positioning of the sliding block and swivel-in sliding block

Spring	Slot		No.
Spring steel, stainless	6	100	3 842 523 145
	8	100	3 842 516 685
	10	100	3 842 516 669