

NSYDS3D46T

Glazed door for Spacial S3D H400xW600 RAL 7035, with lock



Main

| | |
|------------------------------------|--------------------------|
| Range | Spacial |
| Accessory / separate part category | Enclosure accessory |
| Product or component type | Door |
| Device application | Multi-purpose |
| For enclosure nominal dimensions | |
| Mounting location | Front |
| Range compatibility | Spacial S3D |
| Device composition | 1 door Locking system |
| Quantity per set | Set of 1 |

Complementary

| | |
|-----------------|--------------------------|
| Material | Sheet steel for door |
| Colour | Grey RAL 7035 |
| Surface finish | Textured epoxy polyester |
| Lock type | Lock 3 mm double bar |
| Number of locks | 1 |
| Door type | Glazed |
| Door opening | Reversible 120 ° |
| Height | Nominal : 400 mm |
| Width | Nominal : 600 mm |

Environment

Offer Sustainability

| | |
|--------------------------|---------------------------|
| Sustainable offer status | Not Green Premium product |
|--------------------------|---------------------------|

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.