


T-nut







- ▶ Standard element for secure, conductive connections
- ▶ Stop for correct positioning in the profile slot
- ▶ Stainless steel T-nuts, e.g. for outdoor or cleanroom applications
- ▶ Profile finishing: not required


Technical data (p. 19-5)


Accessories:
Insulating cap (p. 3-5)











Slot	
6	1700 N


T-nut, 6 mm slot	Slot	M	ESD		No.
Steel, galvanized	6	M4		100	3 842 523 135
Steel, stainless	6	M4		100	3 842 536 599












Slot	
8 (M6)	4000 N

T-nut, 8 mm slot	Slot	M	ESD		No.
Steel, galvanized	8	M4		100	3 842 501 751
		M5		100	3 842 501 752
		M6		100	3 842 501 753
Steel, stainless	8	M4		100	3 842 536 600
		M5		100	3 842 536 601
		M6		100	3 842 536 602



Slot	
10 (M8)	6000 ... 18,000 N ¹⁾

¹⁾ Depending on profile (p. 19-5)

T-nut, 10 mm slot	Slot	M	ESD		No.
Steel, galvanized	10	M4		100	3 842 530 281
		M5		100	3 842 530 283
		M6		100	3 842 530 285
		M8		100	3 842 530 287
Steel, stainless	10	M4		100	3 842 536 606
		M5		100	3 842 536 605
		M6		100	3 842 536 604
		M8		100	3 842 536 603