

## Sheetsteel housing **BGUK 20**



### Advantages

- Integrated Rail System for the installation of different product sizes
- Excellent corrosion protection and high abrasion resistance through powder-coated surface RAL 5008
- With cooling fins for optimal heat extraction
- Faceplate without cooling fins for individual connection options
- Integrated crane eyes
- Optionally available in degree of protection IP 54

### Approvals



## Sheetsteel housing BGUK 20

| Type            |  | BGUK 20 |
|-----------------|--|---------|
| Electrical data | Operating data                                 |         |
|                 | For power (single phase)                       | 2500 VA |
|                 | For power (three phase)                        | 1500 VA |
|                 | Max. Power loss (at 40 °C ambient temperature) | 240 W   |
|                 | Enclosure suitable for protection index        | IP 23   |
| Order numbers   |  |         |
| Order Number    |  | BGUK 20 |

| Type                           |                                | BGUK 20         |
|--------------------------------|--------------------------------|-----------------|
| Mechanical data                | Terminal and mounting          |                 |
|                                | Floor mounting                 | Yes             |
|                                | Wall mounting                  | Yes             |
|                                | Cable glanding type            | M25             |
|                                | Cable glanding Ø               | 9 - 14 mm       |
|                                | Measures and weights           |                 |
|                                | Weight                         | 12.00 kg        |
|                                | Dimension (W x H x D)          | 420 x 365 x 230 |
|                                | Effective inside dimension (W) | 305 mm          |
|                                | Effective inside dimension (D) | 185 mm          |
| Effective inside dimension (H) | 290 mm                         |                 |
| Fixing hole Ø                  | 9 mm                           |                 |
| Accessory                      |                                |                 |
| Front plate (optional)         | BGUKF 20                       |                 |