NSYS3DEX6425

Spacial S3DEX (ATEX certified) H600xW400xD250 .IP66 IK10 RAL7035.





Main

Range	Spacial	
Product name	Spacial S3DEX	
Device application	ATEX certified application	
Product or component type	Compact enclosure	
Enclosure nominal height	600 mm	
Enclosure nominal width	400 mm	
Enclosure nominal depth	250 mm	
Door type	Plain	
Mounting plate description	Without mounting plate	
Type of gland plate	Without gland plate	
Installation accessory type	Wall-mounting	
Product destination	For potentially explosive atmosphere	
Device composition	Lock 1 Door 1 Body with clamped blind nut	

Complementary

Variant particularity	Gutter-shaped front rail double sheet thickness Single piece body	
Number of doors	1 front face	
Door opening	Reversible 120 °	
Lock type	3 points lock, 3 mm double-bar	
Accessibility for operation	Front	
Removable parts	Door by hinges	
Material	Steel	
Surface finish	Epoxy-polyester powder	
Colour	Grey RAL 7035	
Standards	EN 60079-0: 2012 EN 60079-7: 2007 EN 60079-31: 2009	
Marking	II 2 GD Ex e IIC Gb Ex tb IIIC Db according to the ATEX directive 94/9/EC	

Environment

IP degree of protection	IP66 enclosures with single door conforming to IEC 60529	o
IK degree of protection	IK10 conforming to IEC 62262	

Offer Sustainability

Sustainable offer status	Green Premium product	tro
RoHS (date code: YYWW)	Compliant - since 0940 - Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
Product end of life instructions	Need no specific recycling operations	

Contractual warranty

Contractan warranty		
Warranty period	18 months	