

## NSYPLM3025G

wall-mounting enclosure polyester monobloc IP66  
H308xW255xD160mm



### Main

Range	Thalassa
Product name	Thalassa PLM
Device short name	PLM
Device application	Multi-purpose
Product or component type	Compact enclosure
Enclosure nominal height	308 mm
Enclosure nominal width	255 mm
Enclosure nominal depth	160 mm
Enclosure mounting	Wall mounted
Device composition	Lock 2 Door 1 Body 1
Body type	Single piece body
Door type	Plain
Lock type	3 mm double-bar lock

### Complementary

Number of locks	2
Mounting plate description	Without mounting plate
Accessibility for operation	Front
Removable parts	Door by hinges
Material	Polyester reinforced with fibreglass
Colour	Grey RAL 7035
Standards	IEC 62208 NEMA classification 13 NEMA classification 4X
Product certifications	UL

### Environment

IP degree of protection	IP66 IEC 60529
IK degree of protection	IK10 IEC 62262
fire resistance	960 °C IEC 62208
ambient air temperature for storage	-35...90 °C

### Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1511 - Schneider Electric declaration of conformity

### Contractual warranty

Warranty period	18 months
-----------------	-----------