


FEMALE CONTACT CAT. N°	FIG.	Z	Y	WIRE SIZE		WIRE INSUL. DIAM. IN MM.	WIRE STRIP LENGTH IN MM.	HAND CRIMP TOOLING		EXTRACTION TOOL
				AWG	MM ²			DIE SET	HANDTOOL FOR LOOSE PIECE	
SC24M1* / SC24M1*REV	4A			26/24	0.12/0.25	0.90/1.60	4.0	S16SCM20	HANDLES	RX20256E1
SC24ML1*	4B									
SC20M1* / SC20M1*REV	3A			22/20	0.32/0.50	1.20/2.10	4.0	S16SCM20	HANDLES	
SC20ML1*	3B									
SC16M11* / SC16M11*REV	2A			18/16	0.82/1.50	3.0 Max	4.65	S16SCML11	HANDLES	
SC16ML11*	2B									
SC16M1* / SC16M1*REV	1A	2.87	2.3	18/16	0.82/1.50	3.2 Max	6.35	S16SCML1	HANDLES	
SC16ML1*	1B									
SC14M1* / SC14M1*REV	1A	3.3	3.3	14	2.10/2.50	3.2 Max	6.35	S16SCML1	HANDLES	
SC14ML1*	1B									



- * PLATING
- : S6 = 0.75 μ GOLD MIN. OVER Ni (AREA 1)
 - : GOLD FLASH OVER Ni (AREA 2)
 - : D70 = 0.13 μ GOLD MIN. OVER Ni (AREA 1) For standard winding
 - : GOLD FLASH OVER Ni (AREA 2)
 - : TK6 = 0.5-2.5 μ Sn PRE-PLATED (AREA 1+ 2)
 - : S1B = 0.75 μ GOLD MIN OVER Ni (AREA 1)
 - : 1,3 μ MINI Sn OVER Ni (AREA 3)
 - : 1,3 μ MINI Ni (AREA 4)
 - : S31 = GOLD FLASH OVER Ni (AREA 1)
 - : 1,3 μ MINI Sn OVER Ni (AREA 3) For standard winding only
 - : 1,3 μ MINI Ni (AREA 4)
 - : D70REV = 0.13 μ GOLD MIN. OVER Ni (AREA 1)
 - : 1,3 μ MINI Sn OVER Ni (AREA 3) For reverse winding
 - : 1,3 μ MINI Ni (AREA 4)

SEE FIG.1B-2B-3B-4B

SEE FIG.1B-2B-3B-4B

CONSTRUCTION

CONTACT BODY : HIGH CONDUCTIVITY COPPER ALLOY.
OUTER SPRING : STAINLESS STEEL.

PACKING CONTACTS ON STANDARD STRIP : 3000 PCS. PER REEL, E.G. SC16M11*
PACKING CONTACTS ON REVERSE STRIP : 3000 PCS. PER REEL, E.G. SC16M11*REV
FOR WINDING DIRECTION ON REEL (STANDARD OR REVERSE) : SEE BS.C.202338.004

PACKING LOOSE PIECE CONTACTS : 100 PCS PER STD. PACKING. E.G. SC16ML11*

CONNECTOR ACCOMMODATION

THESE CONTACTS CAN BE USED IN ANY CONTACT POSITION IN ANY CONNECTOR IN THE TRIM TRIO INTERCONNECTION SYSTEM : MSM - MSG - MB RECTANGULAR CONN. , SMS QIKMATE CONN. , UTO - UTS - UTL - UTG AND UTP - MBG CIRCULAR CONN.

PERFORMANCE CHARACTERISTICS

CURRENT RATING : 13 A CONTACT RETENTION IN BODY : 65 N MIN.
CONTACT RESISTANCE : <= 6 m Ohm INDIVIDUAL INSERTION FORCE : 3,5 N MAX.
OPERATING VOLTAGE : 750 V RMS INDIVIDUAL WITHDRAWAL FORCE : 0,55 N MIN.

CUSTOMER DRAWING

D 18/02/19	UPDATE HAND CRIMP TOOLING ADD DETAIL FOR HEACH P/N SC--ML--*	ROUILLARD	LEGER	-
IND. DATE	LIBELLE	REVIS	DATE	CONTROLE PAR (MODIFICATION)
DEFINI PAR : R. Vorbeek	LE:11-06-86	TYPE DE PLAN: CUSTOMER DRAWING		
VERIFIE PAR : -	LE: -			
LES COTES S'ENTENDENT AVANT PROTECTION / FINITION				
DENOMINATION: FEMALE FORMED TWO PIECE CONTACT				
SC--M--				
ECHELLE	TOLERANCES GENERALES	MATIERE: -	N°: -	
1/1	ANGULAIRES: ± - °	PROTECTION: -	CODE: -	
	LINEAIRES: ± -	DEFIANTS DE GEOMETRIE	REFERENCE MATERIEL	AFFAIRE
	ETAT DE SURFACE	VOIR NF E 04-502	-	TT
SOURIAU		www.souriau.com		CE DOCUMENT EST LA PROPRIETE DE SOURIAU
FORMAT	REFERENCE PLAN			FOLIO
A1	BS-C-200178-002			1/1