

General accessories – Contacts for plastic and metal circular connectors

TT93

	Ø Wire (mm ² /inch ²)	AWG	Ø Isolator (mm/inch)	Shell Size					
				11	17	23	Contacts		
				4	9	14	24	37	
26	0,05-0,14 0.00008-0.00022	26-30	0,4-0,8 0.02-0.03	○	○	○	○	○	
24	0,14-0,25 0.00021-0.00039	24-26	0,8-1,4 0.03-0.06	○	○	○	○	○	
21	0,25-0,5 0.00039-0.00078	20-24	2,0-2,5 0.08-0.1	○	○	○	○	○	
20	0,25-0,5 0.00039-0.00078	20-24	1,1-1,8 0.04-0.07	○	○	○	○	○	
17	0,75-1,5 0.00116-0.00233	16-18	2,0-3,5 0.08-0.14	A	○	A	○	A	
16	0,75-1,5 0.00116-0.00233	16-18	2,0-2,5 0.08-0.1	○	○	○	○	○	
14	1,5-2,5 0.00233-0.00388	14-16	2,0-4,0 0.08-0.16	A	○	A	○	A	
13	2,5-4,0 0.00388-0.00620	12-14	2,8-4,2 0.11-0.17	A	B	A	B	A	
12	2,5-4,0 0.00388-0.00620	12-14	2,8-3,5 0.11-0.14	A	○	A	○	A	

Contact Type		Coating	
P	Pin	T	Tin Matt
S	Socket	G	Gold 0,38µm
G	Early Make Pin	U	Tin Bright
		H	Gold 0,75µm
		I	Gold Flash

	Packaging	Coil Direction
2	Loose piece contacts 500 pcs	-
3	Reeled 5000 pcs Pin AWG 12-14 – Socket AWG 14-16 & AWG 12-14 on coil 3000 pcs	A
4	See Section 3	B
5	See Section 3	C
6	See Section 3	D

