

**Product information**
GML 209 NJ GB1 LED 24 schwarz/black
933 642-100

Name	
GML 209 NJ GB1 LED 24 schwarz/black	
	
Bridge-type rectifier with protective circuit (varistor) and function indicator (LED)	
Delivery informations	
Availability	available
Product description	
Description	Bridge-type rectifier with protective circuit (varistor) and function indicator (LED)
Type	GML 209 NJ GB1 LED 24 schwarz/black
Order No.	933 642-100
Other standard types	transparent housing, cable gland grey: Order No. 933 642-106
Number of contacts	2 + PE
Cable gland	PG 9 (black)
Conductor size	max. 0.75 mm ²
Standard	industrial standard (11 mm)
Housing Color	transparent
Construction type	B
Description of Wiring	
LED color	LED red
Voltage rectifier	bridge-type rectifier
Suppressor	Varistor
Technical data	
Pin dimensions	6.3 mm x 0.8 mm
Rated voltage	AC/DC 24 V
Rated current	2 A (SEV 1011 : 1,5 A) AC / 1 A DC
Contact resistance	<= 4 mOhm
Type of termination	screw / cable shoe / cable eye
Suitable cables	4.5 mm to 7 mm diameter
Mounting	central screw
Material	
Contact surface material	Sn
Contact bearer material	PA
Housing material	PA
Environmental conditions	
Protection class (IEC 60529)	IP 65
Pollution severity	3
Temperature range	-40 °C to +90 °C
Inflammability class	
Housing	94 V-1
Contact bearer	94 HB
Approvals	
UR	UR
VDE	VDE
Packing unit	
Packaging unit	50 pieces

Picture

Drawing

