

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT - new logo 2011

ALL RIGHTS RESERVED.

LOC
HDIST
-

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	E	CHANGES PER ECR-11-005299	14MAR2011	PP	JK
	F	CHANGES PER ECR-11-006548	21OCT2011	PP	JK
	G	CHANGES PER ECR-12-004118	02MAR2012	PP	JK
	G1	CHANGES PER ECR-13-013257	30AUG2013	RS	DD

NOTES:

1 CONNECTOR ACCEPT MULTIPLE WIRES SIZES: SEE TABLE.

2 HOUSING AND BUTTON MATERIAL : POLYCARBONATE

3 IDC CONTACT MATERIAL: PhBR


4 PRINTING LOGO'S: P/N 293545-1 and -2: UL, ENEC, KEMA, PARTNUMBER, TE.

5 PRINTING LOGO'S: P/N 293545-3 and -4: UL, PARTNUMBER, TE.

6 WIRE INSULATION DIAMETER RANGE IS FROM 1.75 TO 2.85 mm

SEE NOTE 4 & 5

HOUSING COLOR	PARTNUMBER	DESCRIPTION	CABLE SIZE
YELLOW TRANSPARENT	293545-4	SPLICING CONNECTOR SEALED	AWG 20 (0.52mm ²) / AWG 22 (0.33mm ²)
	293545-3	SPLICING CONNECTOR UNSEALED	AWG 20 (0.52mm ²) / AWG 22 (0.33mm ²)
NATURAL TRANSPARENT	293545-2	SPLICING CONNECTOR SEALED	AWG 18 (0.82mm ²) TO 1mm ²
	293545-1	SPLICING CONNECTOR UNSEALED	AWG 18 (0.82mm ²) TO 1mm ²

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 04MAR2010 J.v.d.Krogt	 TE Connectivity SPLICING CONNECTOR	
DIMENSIONS: mm		CHK 04MAR2010 J.v.d.Krogt		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD 06MAR2010 O.Leijnse		
0 PLC ± 1 PLC ±0.2 2 PLC ±0.15 3 PLC ± 4 PLC ± ANGLES ±3°		PRODUCT SPEC 108-19419		
MATERIAL SEE NOTES		FINISH SEE NOTES	APPLICATION SPEC 114-19136	NAME
		WEIGHT -	SIZE A3	CAGE CODE 00779
		CUSTOMER DRAWING	DRAWING NO C-293545	RESTRICTED TO -
			SCALE 2:1	SHEET 1 OF 1
				REV G1

1470-19 (3/11)