

Photointerrupter, Ultraminiature SMD type



Absolute maximum ratings (Ta=25°C)

Parameter	Symbol	Limits	Unit
Input (LED)	Forward current	I <sub>F</sub>	50 mA
	Reverse voltage	V <sub>R</sub>	5 V
	Power dissipation	P <sub>D</sub>	80 mW
Output (photo-transistor)	Collector-emitter voltage	V <sub>CEO</sub>	30 V
	Emitter-collector voltage	V <sub>ECO</sub>	4.5 V
	Collector current	I <sub>C</sub>	30 mA
	Collector power dissipation	P <sub>C</sub>	80 mW
	Operating temperature	T <sub>opr</sub>	-30 to +85
Storage temperature	T <sub>stg</sub>	-40 to +85	°C

Applications

- DSC(Digital steal camera)
- DVC(Digital video camera)
- Digital handy phone

Features

- 1) Ultraminiature middle size SMD type.
- 2) Gap 1.2mm.

Electrical and optical characteristics (Ta=25°C)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions	
Input charac-teristics	Forward voltage	V <sub>F</sub>	1.8	2.3	V	I <sub>F</sub> =50mA	
	Reverse current	I <sub>R</sub>	-	10	μA	V <sub>R</sub> =5V	
	Dark current	I <sub>CEO</sub>	-	0.1	μA	V <sub>CE</sub> =10V	
Output charac-teristics	Peak sensitivity wavelength	λ <sub>P</sub>	800	-	nm	-	
	Collector current	I <sub>C</sub>	0.1	-	mA	V <sub>CE</sub> =5V, I <sub>F</sub> =5mA	
Transfer characteristics	Collector-emitter saturation voltage	V <sub>CE(sat)</sub>	0.4	-	V	I <sub>F</sub> =20mA, I <sub>C</sub> =0.1mA	
	Response time	Rise time	t <sub>r</sub>	30	150	μs	V <sub>CC</sub> =5V, I <sub>F</sub> =0.1mA, R <sub>L</sub> =1000Ω
		Fall time	t <sub>f</sub>	30	150	μs	
Infrared light emitter diode	Peak light emitting wavelength	λ <sub>P</sub>	850	-	nm	I <sub>F</sub> =50mA * Non-coherent Infrared light emitting diode used.	
	Response time	t <sub>r</sub> -t <sub>f</sub>	50	-	μs	V <sub>CC</sub> =5V, I <sub>C</sub> =0.1mA, R <sub>L</sub> =1000Ω * This product is not designed to be protected against electromagnetic wave.	
Photo transistor	Maximum sensitivity wavelength	λ <sub>P</sub>	800	-	nm	-	

Electrical and optical characteristics curves




Fig.4 Relative output current vs. distance (II)




Fig.2 Forward current falloff




Fig.3 Forward current vs. forward voltage




Fig.1 Relative output current vs. distance (I)




Fig.5 Power dissipation / collector power dissipation vs. ambient temperature




Fig.6 Relative output vs. ambient temperature




Fig.7 Collector current vs. forward current




Fig.8 Response time vs. collector current




Fig.9 Dark current vs. ambient temperature






Fig.10 Output characteristics



t<sub>d</sub>: Delay time  
 t<sub>r</sub>: Rise time (time for output current to rise from 10% to 90% of peak current)  
 t<sub>f</sub>: Fall time (time for output current to fall from 90% to 10% of peak current)

Fig.11 Response time measurement circuit

Dimensions (Unit : mm)



Notes:  
 1. Unspecified tolerance shall be ±0.2.  
 2. Dimension in parenthesis are show for reference.

### Notes

- No technical content pages of this document may be reproduced in any form or transmitted by any means without prior permission of ROHM CO.,LTD.
- The contents described herein are subject to change without notice. The specifications for the product described in this document are for reference only. Upon actual use, therefore, please request that specifications to be separately delivered.
- Application circuit diagrams and circuit constants contained herein are shown as examples of standard use and operation. Please pay careful attention to the peripheral conditions when designing circuits and deciding upon circuit constants in the set.
- Any data, including, but not limited to application circuit diagrams information, described herein are intended only as illustrations of such devices and not as the specifications for such devices. ROHM CO.,LTD. disclaims any warranty that any use of such devices shall be free from infringement of any third party's intellectual property rights or other proprietary rights, and further, assumes no liability of whatsoever nature in the event of any such infringement, or arising from or connected with or related to the use of such devices.
- Upon the sale of any such devices, other than for buyer's right to use such devices itself, resell or otherwise dispose of the same, no express or implied right or license to practice or commercially exploit any intellectual property rights or other proprietary rights owned or controlled by
- ROHM CO., LTD. is granted to any such buyer.
- Products listed in this document are no antiradiation design.

The products listed in this document are designed to be used with ordinary electronic equipment or devices (such as audio visual equipment, office-automation equipment, communications devices, electrical appliances and electronic toys).

Should you intend to use these products with equipment or devices which require an extremely high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), please be sure to consult with our sales representative in advance.

It is our top priority to supply products with the utmost quality and reliability. However, there is always a chance of failure due to unexpected factors. Therefore, please take into account the derating characteristics and allow for sufficient safety features, such as extra margin, anti-flammability, and fail-safe measures when designing in order to prevent possible accidents that may result in bodily harm or fire caused by component failure. ROHM cannot be held responsible for any damages arising from the use of the products under conditions out of the range of the specifications or due to non-compliance with the NOTES specified in this catalog.

Thank you for your accessing to ROHM product informations.

More detail product informations and catalogs are available, please contact your nearest sales office.

**ROHM Customer Support System**

**THE AMERICAS / EUROPE / ASIA / JAPAN**

[www.rohm.com](http://www.rohm.com)

Contact us : [webmaster@rohm.co.jp](mailto:webmaster@rohm.co.jp)



RPI-0226 - Web Page

[Distribution Inventory](#)

Part Number	RPI-0226
Package	PLI
Unit Quantity	2000
Minimum Package Quantity	2000
Packing Type	Taping
Constitution Materials List	inquiry
RoHS	Yes