



Acc. Cam Switches (UK)



Powering Business Worldwide™

Part no.
Article no.

KNB-RT-T0
043655

Delivery programme

Product range			Accessories
			Thumb-grips
Standards			According to IEC/EN 60204-1, VDE 0113 Part 1
			Only for emergency switching off/emergency stop switches
Colour			Red
For use with			T0-.../E, .../IVS, .../Z, .../I1 T3-.../E, .../IVS, .../Z, .../I2 P1-.../E, .../IVS, .../Z, .../I2
Notes	<ul style="list-style-type: none"> Order additional yellow front plate FS908GE-T0 		

Technical data ETIM 4.0

Number of auxiliary contacts as normally open contact			0
Number of auxiliary contacts as normally closed contact			0
Rated permanent current I _u		A	0
Number of poles			0
Conditioned rated short-circuit current I _q		kA	0
Degree of protection (IP), front side			-
Number of auxiliary contacts as change-over contact			0
Interlockable			No
Motor drive integrated			No
Connection type main current circuit			-
Version as emergency stop installation			No
Type of control element			Toggle
Version as main switch			No
Version as switch disconnecter compact			No
Version as safety switch			No
Version as maintenance-/service switch			No
Rated operation power at AC-23, 400V		kWh	0
Rated operation power AC-3, 400 V		kWh	0
Suitable for ground mounting			No
Suitable for front mounting			No
Suitable for front mounting center			No
Suitable for distribution board installation			No
Suitable for intermediate mounting			No
Max. rated operation voltage U _e AC		V	0
Motor drive optional			No
Voltage release optional			No
Device construction			-