

VW3M5D2AR50

power cable 5m shielded 4x 1,3mm², BCH2
MIL connector



Main

Range of product	Lexium 28
Product or component type	Power cable
Accessory / separate part type	Preassembled power cordset
Accessory / separate part category	Connection accessory
Product compatibility	Servo motor BCH2 at 1000 W (100 mm) (without brake) Servo motor BCH2 at 2000 W (100 mm) (without brake) Servo motor BCH2 at 300 W (130 mm) (without brake) Servo motor BCH2 at 500 W (130 mm) (without brake) Servo motor BCH2 at 600 W (130 mm) (without brake) Servo motor BCH2 at 850 W (130 mm) (without brake) Servo motor BCH2 at 900 W (130 mm) (without brake) Servo motor BCH2 at 1000 W (130 mm) (without brake) Servo motor BCH2 at 1500 W (130 mm) (without brake) Servo motor BCH2 at 2000 W (130 mm) (without brake)
Accessory / separate part destination	Between servo motor and servo drive
Range compatibility	Lexium 28
Cable length	5 m

Complementary

Electrical connection	Free end (servo drive side) Connector MIL small (servo motor side)
AWG gauge	4 x AWG 16
Product weight	0.7 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.