

Type 3 surge protection device - PLT-SEC-T3-230-FM - 2905229

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Plug-in device protection, according to type 3/class III, for 1-phase power supply networks with separate N and PE (3-conductor system: L1, N, PE), with integrated surge-proof fuse and remote indication contact.

Why buy this product

- Varistor-based device protection
- Can be used without separate backup fuse thanks to integrated overcurrent protection
- For single-phase power supply units
- Pluggable
- Optical status indicator via LED
- With floating remote indication contact
- Plugs can be checked with CHECKMASTER 2



Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 939881
Weight per Piece (excluding packing)	73.33 g
Custom tariff number	85363030
Country of origin	Germany

Technical data

Dimensions

Height	90 mm
Width	17.7 mm
Depth	74.5 mm
Horizontal pitch	1 Div.

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-40 °C ... 80 °C
Ambient temperature (storage/transport)	-40 °C ... 80 °C

Type 3 surge protection device - PLT-SEC-T3-230-FM - 2905229

Technical data

Ambient conditions

Altitude	≤ 2000 m (amsl (above mean sea level))
Permissible humidity (operation)	5 % ... 95 %
Shock (operation)	30g (half sinus / 11 ms / 3x ±X, ±Y, ±Z)
Vibration (operation)	5g (10 ... 150 Hz/20 cycles/axis/X, Y, Z)

General

Standards/specifications	IEC 61643-11 2011
	EN 61643-11 2012
IEC test classification	III
	T3
EN type	T3
IEC power supply system	TT
	TN-S
Number of ports	One
SPD design	Combination type
Mode of protection	L-N
	L-PE
	N-PE
	(L+) - (L-)
	(L+/L-) - PE
Mounting type	DIN rail: 35 mm
Color	light grey RAL 7035
	traffic grey A RAL 7042
Housing material	PA 6.6-FR 20% GF
	PA 6.6-FR
Pollution degree	2
Inflammability class according to UL 94	V-0
Type	DIN rail module, two-section, divisible
Number of positions	2
Surge protection fault message	Optical, remote indicator contact

Protective circuit

Nominal voltage U_N	230 V AC (TN-S)
	230 V AC (TT - only in use with RCD)
Nominal frequency f_N	50 Hz (60 Hz)
Maximum continuous voltage U_C	264 V AC
	230 V DC
Rated load current I_L	26 A (30 °C)
Residual current I_{PE}	≤ 5 μA
Nominal discharge current I_n (8/20) μs	3 kA
Standby power consumption P_C	≤ 275 mVA (at U_{REF})

Type 3 surge protection device - PLT-SEC-T3-230-FM - 2905229

Technical data

Protective circuit

	≤ 300 mVA (at U _C)
Reference test voltage U _{REF}	255 V AC
Combination wave U _{OC}	6 kV
Voltage protection level U _p (L-N)	≤ 1.35 kV
Voltage protection level U _p (L-PE)	≤ 1.5 kV
Voltage protection level U _p (N-PE)	≤ 1.5 kV
TOV behavior at U _T (L-N)	440 V AC (5 s / withstand mode)
	440 V AC (120 min / withstand mode)
TOV behavior at U _T (L-PE)	440 V AC (5 s / withstand mode)
	440 V AC (120 min / withstand mode)
	1455 V AC (200 ms / safe failure mode)
TOV behavior at U _T (N-PE)	1200 V AC (200 ms / safe failure mode)
Response time t _A (L-N)	≤ 25 ns
Response time t _A (L-PE)	≤ 100 ns
Response time t _A (N-PE)	≤ 100 ns
Short-circuit current rating I _{SCCR}	1.5 kA AC
	0.25 kA DC
Max. backup fuse with branch wiring	Not required
Maximum backup fuse for through wiring	25 A (gG / B / C)

Indicator/remote signaling

Connection name	Remote fault indicator contact
Switching function	N/C contact
Operating voltage	250 V AC
	125 V DC (200 mA DC)
Operating current	3 A AC
	1 A DC (30 V DC)
Connection method	Screw connection
Screw thread	M3
Tightening torque	0.8 Nm
Stripping length	8 mm
Conductor cross section flexible min.	0.2 mm ²
Conductor cross section flexible max.	2.5 mm ²
Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	4 mm ²
AWG conductor cross section	24 ... 12

Connection data

Connection method	Screw connection
Conductor cross section flexible min.	0.2 mm ²
Conductor cross section flexible max.	2.5 mm ²

Type 3 surge protection device - PLT-SEC-T3-230-FM - 2905229

Technical data

Connection data

Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	4 mm ²
AWG conductor cross section	24 ... 12 (IEC)
	24 ... 12 (UL)
Screw thread	M3
Tightening torque	0.8 Nm
Stripping length	8 mm

UL specifications

UL class	SPD type 4CA
Maximum continuous operating voltage MCOV	255 V AC
	230 V DC
Nominal voltage	230 V DC
Mode of protection	L-N
	L-G
	N-G
	(L+) - (L-)
	(L+) - G
	(L-) - G
Power distribution system	1
Nominal frequency	50/60 Hz
Measured limiting voltage MLV (L-N)	1270 V
Measured limiting voltage MLV (L-G)	1280 V
Measured limiting voltage MLV (N-G)	1208 V
Measured limiting voltage MLV (L+) - (L-)	1270 V
Measured limiting voltage MLV (L+) - G	1280 V
Measured limiting voltage MLV (L-) - G	1280 V
Nominal discharge current I _n	3 kA

Classifications

eCl@ss

eCl@ss 5.1	27130801
eCl@ss 6.0	27130806
eCl@ss 8.0	27130803

ETIM

ETIM 5.0	EC000942
----------	----------

Approvals

Approvals

Type 3 surge protection device - PLT-SEC-T3-230-FM - 2905229

Approvals

Approvals

KEMA-KEUR / CCA / IECCE CB Scheme / UL Recognized / cUL Recognized / EAC / GL / cULus Recognized

Ex Approvals


UL Recognized / cUL Recognized / cULus Recognized

Approvals submitted


Approval details

KEMA-KEUR 

CCA


IECEE CB Scheme 

UL Recognized 

cUL Recognized 

EAC


GL

cULus Recognized 

Drawings


Type 3 surge protection device - PLT-SEC-T3-230-FM - 2905229

Diagram



Nominal current depending on ambient temperature


Dimensional drawing



Product drawing



Circuit diagram



Type 3 surge protection device - PLT-SEC-T3-230-FM - 2905229

Application drawing

