



Main

Device short name	LUL
Range of product	TeSys U
Product or component type	Communication module
Product compatibility	LUCA LUCB LUCC LUCD LUCL LUCM

Complementary

Main function available	Communication module
Mounting mode	Plug-in
Mounting location	Front side
Physical interface	RS485 multidrop
Bus type	Modbus
Cable connector type	RJ45 front panel
Communication port protocol	Modbus RTU
Addressing	0...31
Transmission rate	19200 bit/s
Return time	30 ms
Number of inputs	2
Input logic	Positive at 24 V DC - 7 mA
Response time	10 ms +/- 30 % change to state 0 10 ms +/- 30 % change to state 1
Input type	Resistive
Number of outputs	1 2 dedicated to starter-controller coil operation
Output supply	24 V DC network
Output current	<= 500 mA
Protection type	GG fuse 1 A
Switching current capacity	0.5 mA at 24 V
Local signalling	3 LEDs front panel
Connection pitch	3.81 mm
Connections - terminals	Screw clamp terminals 1 cable 0.14...1 mm ² - cable stiffness: flexible - without cable end Screw clamp terminals 1 cable 0.14...1 mm ² - cable stiffness: rigid - without cable end Screw clamp terminals 1 cable 0.25...0.5 mm ² - cable stiffness: flexible - with cable end Screw clamp terminals 1 cable 0.25...1 mm ² - cable stiffness: flexible - with cable end Screw clamp terminals 2 cable 0.14...0.5 mm ² - cable stiffness: rigid - without cable end Screw clamp terminals 2 cable 0.14...0.75 mm ² - cable stiffness: flexible - without cable end Screw clamp terminals 2 cable 0.25...0.34 mm ² - cable stiffness: flexible - with cable end Screw clamp terminals 2 cable 0.5 mm ² - cable stiffness: flexible - with cable end
Associated cable type	AWG 26...AWG 16

Tightening torque	0.2...0.25 N.m - with screwdriver 2.5 mm
Product weight	0.08 kg

Environment

Ambient air temperature for operation	-25...55 °C
---------------------------------------	-------------
