

1a 10A, 1a1b/2a 8A small polarized power relays

DK RELAYS



Compliance with RoHS Directive

FEATURES

- 1. Compact with high capacity**
High capacity switching in a small package: 1 Form A, 10 A 250 V AC; 1 Form A 1 Form B and 2 Form A, 8 A 250 V AC.
- 2. High sensitivity: 200 mW nominal operating power**
- 3. High breakdown voltage**
Independent coil and the contact structure improves breakdown voltage.

| Between contact and coil | Between open contacts |
|--|---|
| 4,000 Vrms for 1 min. 10,000 V surge breakdown voltage | 1,000 Vrms for 1 min. 1,500 V surge breakdown voltage |

Conforms with FCC Part 68

- 4. Latching types available**
- 5. Sealed construction allows automatic washing.**
- 6. Sockets are available**
- 7. Complies with safety standards**
Complies with Japan Electrical Appliance and Material Safety Law requirements for operating 200 V power supply circuits, and complies with UL, CSA, and TÜV safety standards.

TYPICAL APPLICATIONS

1. Switching power supply
2. Power switching for various OA equipment
3. Control or driving relays for industrial machines (robotics, numerical control machines, etc.)
4. Output relays for programmable logic controllers, temperature controllers, timers and so on.
5. Home appliances

ORDERING INFORMATION

DK - - -

Contact arrangement

1a: 1 Form A

2a: 2 Form A

1a1b: 1 Form A 1 Form B

Operating function

Nil: Single side stable

L2: 2 coil latching

Nominal coil voltage (DC)

3, 5, 6, 9, 12, 24V

Contact material

F: 1 Form A (AgSnO₂ type)

Nil: 2 Form A, 1 Form A 1 Form B (Au-flashed AgNi type)

Notes: 1. Certified by UL, CSA and TÜV

2. VDE approved type is available.

TYPES

| Contact arrangement | Nominal coil voltage | Single side stable | 2 coil latching |
|----------------------|----------------------|--------------------|-----------------|
| | | Part No. | Part No. |
| 1 Form A | 3V DC | DK1a-3V-F | DK1a-L2-3V-F |
| | 5V DC | DK1a-5V-F | DK1a-L2-5V-F |
| | 6V DC | DK1a-6V-F | DK1a-L2-6V-F |
| | 9V DC | DK1a-9V-F | DK1a-L2-9V-F |
| | 12V DC | DK1a-12V-F | DK1a-L2-12V-F |
| | 24V DC | DK1a-24V-F | DK1a-L2-24V-F |
| 1 Form A 1 Form B | 3V DC | DK1a1b-3V | DK1a1b-L2-3V |
| | 5V DC | DK1a1b-5V | DK1a1b-L2-5V |
| | 6V DC | DK1a1b-6V | DK1a1b-L2-6V |
| | 9V DC | DK1a1b-9V | DK1a1b-L2-9V |
| | 12V DC | DK1a1b-12V | DK1a1b-L2-12V |
| | 24V DC | DK1a1b-24V | DK1a1b-L2-24V |
| 2 Form A | 3V DC | DK2a-3V | DK2a-L2-3V |
| | 5V DC | DK2a-5V | DK2a-L2-5V |
| | 6V DC | DK2a-6V | DK2a-L2-6V |
| | 9V DC | DK2a-9V | DK2a-L2-9V |
| | 12V DC | DK2a-12V | DK2a-L2-12V |
| | 24V DC | DK2a-24V | DK2a-L2-24V |

Standard packing: Carton: 50 pcs.; Case: 500 pcs.

* For sockets, see page 135.

RATING

1. Coil data

1) Single side stable

| Nominal coil voltage | Pick-up voltage (at 20°C 68°F) | Drop-out voltage (at 20°C 68°F) | Nominal operating current [±10%] (at 20°C 68°F) | Coil resistance [±10%] (at 20°C 68°F) | Nominal operating power | Max. applied voltage (at 20°C 68°F) |
|----------------------|---|---|---|---------------------------------------|-------------------------|-------------------------------------|
| 3V DC | 70%V or less of nominal voltage (Initial) | 10%V or more of nominal voltage (Initial) | 66.6mA | 45Ω | 200mW | 130%V of nominal voltage |
| 5V DC | | | 40mA | 125Ω | | |
| 6V DC | | | 33.3mA | 180Ω | | |
| 9V DC | | | 22.2mA | 405Ω | | |
| 12V DC | | | 16.6mA | 720Ω | | |
| 24V DC | | | 8.3mA | 2,880Ω | | |

2) 2 coil latching

| Nominal coil voltage | Set voltage (at 20°C 68°F) | Reset voltage (at 20°C 68°F) | Nominal operating current [±10%] (at 20°C 68°F) | | Coil resistance [±10%] (at 20°C 68°F) | | Nominal operating power | | Max. applied voltage (at 20°C 68°F) |
|----------------------|---|---|---|------------|---------------------------------------|------------|-------------------------|------------|-------------------------------------|
| | | | Set coil | Reset coil | Set coil | Reset coil | Set coil | Reset coil | |
| 3V DC | 70%V or less of nominal voltage (Initial) | 70%V or less of nominal voltage (Initial) | 66.6mA | 66.6mA | 45Ω | 45Ω | 200mW | 200mW | 130%V of nominal voltage |
| 5V DC | | | 40mA | 40mA | 125Ω | 125Ω | | | |
| 6V DC | | | 33.3mA | 33.3mA | 180Ω | 180Ω | | | |
| 9V DC | | | 22.2mA | 22.2mA | 405Ω | 405Ω | | | |
| 12V DC | | | 16.6mA | 16.6mA | 720Ω | 720Ω | | | |
| 24V DC | | | 8.3mA | 8.3mA | 2,880Ω | 2,880Ω | | | |

2. Specifications

| Characteristics | Item | Specifications | | |
|----------------------------|---|---|---|---------------------------|
| | | 1 Form A | 1 Form A 1 Form B | 2 Form A |
| Contact | Arrangement | | | |
| | Contact resistance (Initial) | Max. 30 mΩ (By voltage drop 6 V DC 1A) | | |
| Rating | Contact material | Au-flashed AgSnO ₂ type | | Au-flashed AgNi type |
| | Nominal switching capacity (resistive load) | 10 A 250 V AC, 10 A 30 V DC | 8 A 250 V AC, 8 A 30 V DC | 8 A 250 V AC, 8 A 30 V DC |
| | Max. switching power (resistive load) | 2,500VA, 300 W | 2,000 VA, 240 W | 2,000 VA, 240 W |
| | Max. switching voltage | 250 V AC, 125 V DC | 250 V AC, 125 V DC | 250 V AC, 125 V DC |
| | Max. switching current | 10 A | 8 A | 8 A |
| | Nominal operating power | 200 mW | | |
| | Min. switching capacity (Reference value)*1 | 10m A 5 V DC | | |
| Electrical characteristics | Insulation resistance (Initial) | Min. 1,000MΩ (at 500V DC) Measurement at same location as "Breakdown voltage" section. | | |
| | Breakdown voltage (Initial) | Between open contacts | 1,000 Vrms for 1min. (Detection current: 10mA.) | |
| | | Between contact and coil | 4,000 Vrms for 1min. (Detection current: 10mA.) | |
| | Surge breakdown voltage*2 (Initial) | between contacts and coil | 10,000 V | |
| | Temperature rise (coil) (at 65°C 149°F) | Max. 40°C (By resistive method, nominal voltage applied to the coil; max. switching current) | | |
| Mechanical characteristics | Shock resistance | Functional | Min. 98 m/s ² (Half-wave pulse of sine wave: 11 ms; detection time: 10μs.) | |
| | | Destructive | Min. 980 m/s ² (Half-wave pulse of sine wave: 6 ms.) | |
| | Vibration resistance | Functional | 10 to 55 Hz at double amplitude of 1.5 mm (Detection time: 10μs.) | |
| Destructive | | 10 to 55 Hz at double amplitude of 3 mm | | |
| Expected life | Mechanical | Min. 5×10 ⁷ (at 300 times/min.) | | |
| | Electrical | Min. 10 ⁵ (resistive load, at 20 times/min., at rated capacity) | | |
| Conditions | Conditions for operation, transport and storage*3 | Ambient temperature: -40°C to +65°C -40°F to +149°F, Humidity: 5 to 85% R.H. (Not freezing and condensing at low temperature) | | |
| | Max. operating speed (at rated load) | 20 times/min. | | |
| Unit weight | | Approx. 5 g .18 oz | Approx. 6 g .21 oz | Approx. 6 g .21 oz |


Notes: *1. This value can change due to the switching frequency, environmental conditions, and desired reliability level, therefore it is recommended to check this with the actual load.

*2. Wave is standard shock voltage of $\pm 1.2 \times 50\mu s$ according to JEC-212-1981


*3. The upper limit of the ambient temperature is the maximum temperature that can satisfy the coil temperature rise value. Refer to Usage, transport and storage conditions in NOTES.

REFERENCE DATA


1-(1). Maximum operating power (1 Form A)




1-(2). Maximum operating power (1 Form A 1 Form B, 2 Form A)




2-(1). Life curve (1 Form A)




2-(2). Life curve (1 Form A 1 Form B, 2 Form A)



3-(1). Operate/Release time (1 Form A)
Tested sample: DK1a-24V, 5 pcs.




3-(2). Operate/Release time (1 Form A 1 Form B, 2 Form A)
Tested sample: DK1a1b-12V, 5 pcs.




4-(1). Coil temperature rise (1 Form A)

Tested sample: DK1a-12V, 5 pcs.
Ambient temperature: 30°C 86°F




4-(2). Coil temperature rise (1 Form A 1 Form B, 2 Form A)

Tested sample: DK1a1b-12V, 5 pcs.
Ambient temperature: 20°C 68°F




5-(1). Ambient temperature characteristics (1 Form A)

Tested sample: DK1a-24V, 6 pcs
Ambient temperature: -40°C to +80°C
-40°F to +176°F



5-(2). Ambient temperature characteristics (1 Form A 1 Form B, 2 Form A)



DIMENSIONS (mm inch)


The CAD data of the products with a **CAD Data** mark can be downloaded from: <http://panasonic-electric-works.net/ac>

1. 1 Form A type


CAD Data




External dimensions
Single side stable type



PC board pattern (Bottom view)





Schematic (Bottom view)
Single side stable




(Deenergized condition)

2 coil latching type



2 coil latching



(Reset condition)


General tolerance: $\pm 0.3 \pm 0.012$

Tolerance: $\pm 0.1 \pm 0.004$


Since this is a polarized relay, the connection to the coil should be done according to the above schematic.

2. 1 Form A 1 Form B type, 2 Form A type


CAD Data



External dimensions
Single side stable type





2 coil latching type



General tolerance: $\pm 0.3 \pm .012$


PC board pattern (Bottom view)



Tolerance: $\pm 0.1 \pm .004$


Schematic
(Bottom view)

<1 Form A 1 Form B type>
Single side stable




(Deenergized condition)

2 coil latching




(Reset condition)

<2 Form A>
Single side stable



(Deenergized condition)

2 coil latching



(Reset condition)

Since this is a polarized relay, the connection to the coil should be done according to the above schematic.

SAFETY STANDARDS

| Item | UL/C-UL (Recognized) | | CSA (Certified) | | VDE (Certified) | | TÜV (Certified) | |
|-----------------------------------|----------------------|---|-----------------|---|-----------------|--|---|---|
| | File No. | Contact rating | File No. | Contact rating | File No. | Contact rating | File No. | Rating |
| 1 Form A | E43028 | 10A 250V AC 1/3HP 125, 250V AC 10A 30V DC | LR26550 etc. | 10A 250V AC 1/3HP 125, 250V AC 10A 30V DC | 006099UG | AC 250V 10A (cosφ=1.0) AC 250V 5A (cosφ=0.4) DC 30V 10A (0ms) | 8705 1645 520 | 10A 250V AC (cosφ=1.0) 5A 250V AC (cosφ=0.4) 10A 30V DC |
| 1 Form A 1 Form B, 2 Form A | E43028 | 8A 250V AC 1/4HP 125, 250V AC 8A 30V DC | LR26550 etc. | 8A 250V AC 1/4HP 125, 250V AC 8A 30V DC | 006099UG | 1 Form A 1 Form B: AC 250V 8A (cosφ=1.0) 2 Form A: AC 250V 8A (cosφ=1.0) AC 250V 4A (cosφ=0.4) | 8705 1645 520 (1 Form A 1 Form B) 9407 13461 097 (2 Form A) | 8A 250V AC (cosφ=1.0) 4A 250V AC (cosφ=0.4) 8A 30V DC |

NOTES

1. Soldering should be done under the following conditions:

250°C 482°F within 10s

300°C 572°F within 5s

350°C 662°F within 3s

Soldering depth: 2/3 terminal pitch

2. External magnetic field

Since DK relays are highly sensitive polarized relays, their characteristics will be affected by a strong external magnetic field. Avoid using the relay under that condition.

3. When using, please be aware that the a contact and b contact sides of 1 Form A and 1 Form B types may go on simultaneously at operate time and release time.


For Cautions for Use.



Panasonic
ideas for life

ACCESSORIES

**DK RELAY
SOCKET**



FEATURES

DK relay sockets that can be used also for DY relay.

TYPES

| Type | Part No. | |
|------------------------------|--------------------|-----------|
| 1 Form A | Single side stable | DK1a-PS |
| | 2 coil latching | DK1a-PSL2 |
| 1 Form A 1 Form B, 2 Form A* | Single side stable | DK2a-PS |
| | 2 coil latching | DK2a-PSL2 |

Standard packing: Carton: 50 pcs.; Case: 500 pcs
Note: * 2 Form A type is DK relays only.

Compliance with RoHS Directive

RELAY COMPATIBILITY

| Relay | Socket | 1 Form A | | 1 Form A 1 Form B, 2 Form A | |
|-------------------------------|-------------------------|-------------------------|----------------------|-----------------------------|----------------------|
| | | Single side stable type | 2 coil latching type | Single side stable type | 2 coil latching type |
| 1 Form A | Single side stable type | ● | ● | — | — |
| | 2 coil latching type | — | ● | — | — |
| 1 Form A 1 Form B 2 Form A | Single side stable type | — | — | ● | ● |
| | 2 coil latching type | — | — | — | ● |

SPECIFICATIONS


| Item | Specifications |
|-------------------------|---|
| Breakdown voltage | 4,000 Vrms (Detection current: 10 mA) (Except the portion between coil terminals) |
| Insulation resistance | Min. 1,000 mΩ (at 500 V DC) |
| Heat resistance | 150°C (for 1 hour) |
| Max. continuous current | 10 A (DK1a-PS, DK1a-PSL2), 8 A (DK2a-PS, DK2a-PSL2) |

DIMENSIONS (mm inch)


The CAD data of the products with a **CAD Data** mark can be downloaded from: <http://panasonic-electric-works.net/ac>

CAD Data External dimensions


PC board pattern (Bottom view)



General tolerance: ±0.3 ±.012



The above shows 2 coil latching type. No.2 and 5 terminal are eliminated on single side stable type.




The above shows 2 coil latching type. No.2 and 7 terminal are eliminated on single side stable type.


Tolerance: ±0.1 ±.004

FIXING AND REMOVAL METHOD


1. Match the direction of relay and socket.



2. Both ends of the relay are to be secured firmly so that the socket hooks on the top surface of the relay.




GOOD




NO GOOD

3. Remove the relay, applying force in the direction shown below.



4. In case there is not enough space to grasp relay with fingers, use screwdrivers in the way shown below.



Notes: 1. Exercise care when removing relays. If greater than necessary force is applied at the socket hooks, deformation may alter the dimensions so that the hook will no longer catch, and other damage may also occur.
2. It is hazardous to use IC chip sockets.