


BMTX Nut

Flare Tube End Nut – metric hex
SAE 070110



Tube Ø O.D.		Thread size JIC	C mm	D mm	L mm	Weight (steel)
mm	in.	T6				gr.
6	1/4	7/16-20	14	7.8	15.8	11
8	5/16	1/2-20	17	9.5	14.7	14
10	3/8	9/16-18	19	11.2	15.3	18
12	1/2	3/4-16	22	14.5	18.4	29
14		7/8-14	27	17.8	20.8	54
15		7/8-14	27	17.8	20.8	42
16	5/8	7/8-14	27	17.8	20.8	42
18		1.1/16-12	32	21.2	22.0	73
20	3/4	1.1/16-12	32	21.2	22.0	73
22	7/8	1.3/16-12	35	24.4	27.4	100
25	1	1.5/16-12	41	27.7	24.4	104
28		1.5/8-12	50	34.2	25.8	240
30		1.5/8-12	50	34.2	25.8	240
32	1.1/4	1.5/8-12	50	34.2	25.8	240
35		1.7/8-12	60	41.0	29.7	325
38	1.1/2	1.7/8-12	60	41.0	29.7	325
42		2.1/4	65	48.0	39.7	437

Tube Ø O.D.		Thread size JIC	Triple-Lok steel	Triple-Lok stainless steel	Triple-Lok brass
mm	in.	T6			
6	1/4	7/16-20	4BMTXS	4BMTXSS	4BTXB
8	5/16	1/2-20	5BMTXS	5BMTXSS	5BTXB
10	3/8	9/16-18	6BMTXS	6BMTXSS	6BTXB
12	1/2	3/4-16	8BMTXS	8BMTXSS	8BTXB
14		7/8-14	10BMTXS	10BMTXSS	10BTXB
15		7/8-14	10BMTXS	10BMTXSS	10BTXB
16	5/8	7/8-14	10BMTXS	10BMTXSS	10BTXB
18		1.1/16-12	12BMTXS	12BMTXSS	12BTXB
20	3/4	1.1/16-12	12BMTXS	12BMTXSS	12BTXB
22	7/8	1.3/16-12	14BMTXS	14BTXSS	14BTXB
25	1	1.5/16-12	16BMTXS	16BMTXSS	16BTXB
28		1.5/8-12	20BMTXS	20BMTXSS	20BTXB
30		1.5/8-12	20BMTXS	20BMTXSS	20BTXB
32	1.1/4	1.5/8-12	20BMTXS	20BMTXSS	20BTXB
35		1.7/8-12	24BMTXS	24BMTXSS	24BTXB
38	1.1/2	1.7/8-12	24BMTXS	24BMTXSS	24BTXB
42		2.1/4	28BMTXS	28BTXSS	
50	2	2.1/2-12	32BMTXS	32BTXSS	

Only items priced in current price list are carried in stock.

Design details and specifications subject to change without notice.