



**U025**

## **FLEXIBLE POLYURETHANE TUBING, 25 M ROLLS**

[Description](#)  
[Dimensions](#)  
[Specifications](#)  
[CAD drawings](#)  
[Related products](#)

---

Maximum pressure of polyurethane tubing depends on the temperature, the diameter of the tube and the type of connection used.

<b>working temperature</b>	<b>°C (Celsius)</b>	<b>F (Fahrenheit)</b>	<b>K (Kelvin)</b>
	From -20 to 70	From -4 to 158	From 253 to 343



## U025 FLEXIBLE POLYURETHANE TUBING, 25 M ROLLS



for metric tubing

[Zoom](#)

[Description](#)  
[Dimensions](#)  
[Specifications](#)  
[CAD drawings](#)  
[Related products](#)

convert weight standard : kg | [oz](#)

convert dimensions : mm | [inch](#)

	o.d. (mm)	i.d. (mm)	R (mm)	 (kg)
1025U03 01 18	3	1,8	8,0	0,131
1025U04 01	4	2,5	10,0	0,346
1025U04 02	4	2,5	10,0	0,158
1025U04 03	4	2,5	10,0	0,233
1025U04 04	4	2,5	10,0	0,210
1025U04 05	4	2,5	10,0	0,235
1025U04 06	4	2,5	10,0	0,239
1025U05 01	5	3	13,0	0,378
1025U05 04	5	3	13,0	0,340
1025U06 01	6	4	15,0	0,447
1025U06 02	6	4	15,0	0,480
1025U06 03	6	4	15,0	0,430
1025U06 04	6	4	15,0	0,440
1025U06 05	6	4	15,0	0,480
1025U06 06	6	4	15,0	0,450
1025U08 01	8	5,5	20,0	0,801
1025U08 02	8	5,5	20,0	0,801
1025U08 03	8	5,5	20,0	0,801
1025U08 04	8	5,5	20,0	0,801
1025U08 05	8	5,5	20,0	0,801
1025U08 06	8	5,5	20,0	0,900
1025U10 01	10	7	25,0	1,210
1025U10 02	10	7	25,0	1,210
1025U10 04	10	7	25,0	1,210
1025U10 05	10	7	25,0	1,210
1025U10 06	10	7	25,0	1,210
1025U12 01	12	8	35,0	1,181
1025U12 02	12	8	35,0	1,600
1025U12 04	12	8	35,0	1,562
1025U12 05	12	8	35,0	1,600
1025U12 06	12	8	35,0	2,341
1025U14 01 95	14	9,5	45,0	2,900