


WH-R Full Dimensions

High Pressure Banjo Elbow
24° Flareless / BSPP




TUBE FITTING PART #	END SIZE		h (mm)	I2 (mm)	I3 (mm)	L3 (mm)	S3 (mm)	S6 (mm)	STANDARD Pressure Rating (bar)				
	1 (mm)	2 BSPP							EO			EO-2	
									A3C	71	MS	A3C	71
WH06LR	6	G 1/8 A	2.5	12.0	10.5	24	17	17	250	250	163		250
WH08LR	8	G 1/4 A	3.0	14.5	14.0	30	22	19	250	250	163		250
WH10LR	10	G 1/4 A	3.0	15.5	14.0	30	22	19	250	250	163		250
WH12LR	12	G 3/8 A	3.0	18.0	16.5	36	27	24	250	250	163		250
WH15LR	15	G 1/2 A	4.5	21.5	21.5	45	32	30	250	250	163		250
WH18LR	18	G 1/2 A	4.5	21.0	21.5	45	32	30	250	250	163		250
WH22LR	22	G 3/4 A	3.5	27.5	24.0	53	41	36	160	160			160
WH28LR	28	G 1 A	3.5	32.0	30.5	66	50	46	160	160			160
WH35LR	35	G 1 1/4 A	3.5	36.0	35.5	76	60	55	160	160			160
WH42LR	42	G 1 1/2 A	3.5	40.5	40.5	87	70	60	160	160			160
WH06SR	6	G 1/4 A	3.0	16.5	14.0	30	22	19	315	315	205		315
WH08SR	8	G 1/4 A	3.0	16.5	14.0	30	22	19	315	315	205		315
WH10SR	10	G 3/8 A	3.0	18.5	16.5	36	27	24	315	315	205		315
WH12SR	12	G 3/8 A	3.0	18.5	16.5	36	27	24	315	315	205		315
WH14SR	14	G 1/2 A	4.5	22.5	21.5	45	32	30	315	315			315
WH16SR	16	G 1/2 A	4.5	22.0	21.5	45	32	30	315	315			315
WH20SR	20	G 3/4 A	3.5	26.5	24.0	53	41	36	160	160			160
WH25SR	25	G 1 A	3.5	31.5	30.5	66	50	46	160	160			160
WH30SR	30	G 1 1/4 A	3.5	37.0	34.5	76	60	55	160	160			160
WH38SR	38	G 1 1/2 A	3.5	41.5	40.5	87	70	60	160	160			160

For EO-2 part number, insert "Z" between size and pressure series.
Example: WH06ZLRA3C

- How to Order
- Specs
- Assembly / Installation
- Reference

WH-R-KDS Full Dimensions

High Pressure Banjo Elbow
24° Flareless / BSPP



TUBE FITTING PART #	END SIZE		h (mm)	I2 (mm)	I3 (mm)	L3 (mm)	S3 (mm)	S6 (mm)	STANDARD Pressure Rating (bar)				
	1 (mm)	2 BSPP							EO			EO-2	
									A3C	71	MS	A3C	71
WH06LRKDS	6	G 1/8 A	2.5	12.0	10.5	24	17	17	315	315		315	315
WH08LRKDS	8	G 1/4 A	3.0	14.5	14.0	30	22	19	315	315		315	315
WH10LRKDS	10	G 1/4 A	3.0	15.5	14.0	30	22	19	315	315		315	315
WH12LRKDS	12	G 3/8 A	3.0	18.0	16.5	36	27	24	315	315		315	315
WH15LRKDS	15	G 1/2 A	4.5	21.5	21.5	45	32	30	315	315		315	315
WH18LRKDS	18	G 1/2 A	4.5	21.0	21.5	45	32	30	315	315		315	315
WH22LRKDS	22	G 3/4 A	3.5	27.5	24.0	53	41	36	160	160		160	160
WH28LRKDS	28	G 1 A	3.5	32.0	30.5	66	50	46	160	160		160	160
WH35LRKDS	35	G 1 1/4 A	3.5	36.0	35.5	76	60	55	160	160		160	160
WH42LRKDS	42	G 1 1/2 A	3.5	40.5	40.5	87	70	60	160	160		160	160
WH06SRKDS	6	G 1/4 A	3.0	16.5	14.0	30	22	19	400	400		400	400
WH08SRKDS	8	G 1/4 A	3.0	16.5	14.0	30	22	19	400	400		400	400
WH10SRKDS	10	G 3/8 A	3.0	18.5	16.5	36	27	24	400	400		400	400
WH12SRKDS	12	G 3/8 A	3.0	18.5	16.5	36	27	24	400	400		400	400
WH14SRKDS	14	G 1/2 A	4.5	22.5	21.5	45	32	30	400	400		400	400
WH16SRKDS	16	G 1/2 A	4.5	22.0	21.5	45	32	30	315	315		315	315
WH20SRKDS	20	G 3/4 A	3.5	26.5	24.0	53	41	36	315	315		315	315
WH25SRKDS	25	G 1 A	3.5	31.5	30.5	66	50	46	250			250	
WH30SRKDS	30	G 1 1/4 A	3.5	37.0	34.5	76	60	55	160			160	
WH38SRKDS	38	G 1 1/2 A	3.5	41.5	40.5	87	70	60	160			160	

For EO-2 part number, insert "Z" between size and pressure series.
Example: WH06ZLRKDSA3C

- How to Order
- Specs
- Assembly / Installation
- Reference