



附件




堵栓及其他附件

H2页	铜质堵栓										
0200	0201	0202	0205	0209	0220	0222					
H3页	铁质及不锈钢堵栓										
0216	0210	0206	0285	0285(NPT)							
H4页	铜质转接头										
0143	0144	0152	0145	0158	0117	0123	0136	0191			
H5页	铜质转接头										
0155	0164	0167	0168	0163	0169	0179	0178				
H6页	铜质转接头				H7页	不锈钢转接头					
0121	0121	0192	0121(NPT)	1843	1817	1862	1845	1855			
H8页	不锈钢转接头										
1867(NPT)	1864(NPT)	1861	1821	1863	1821(NPT)	1823	0682	0683			
H9页	消音器										
0674	0670	0675	0676	0672	0671	0677					
I1页	铜镀镍转接头										
0900	0901	0902	0903	0904	0905						
I2页	铜镀镍转接头										
0906	0907	0914-0922	0912	0913-0921	0915	0916-0923	0917-0924	0927	0928		
I3页	铜镀镍转接头										
0909	0908	0910	0911	0918	0919	0931	0920				
I4页	垫圈及分配座										
0138	0602	3310	3312	3311	3313						

铜质堵栓

六角铜质堵栓, BSPP斜螺纹 (即PT斜螺纹) 及公制螺纹

0200




C	
G1/8	0200 10.00
G1/4	0200 13.00

C	
M6x1	0200 52.00
M6x1.25	0200 57.00
M10x1	0200 60.00
M10x1.25	0200 61.00
M12x1	0200 65.00
M12x1.25	0200 66.00
M14x1.5	0200 71.00

六角铜质堵栓, BSPP直螺纹 (即PF直螺纹) 及M5螺纹


0220



C	
M5 x 0.8	0220 19.00
G1/8	0220 10.00
G1/4	0220 13.00
G3/8	0220 17.00
G1/2	0220 21.00

铜质堵栓带六角, BSPP直螺纹 (即PF直螺纹) 及公制螺纹

0201



C	
G3/8	0201 17.00
G1/2	0201 21.00
G3/4	0201 27.00
G1 "	0201 34.00
G1 " 1/4	0201 42.00
G1 " 1/2	0201 49.00

C	
M16x1.5	0201 75.00
M18x1.5	0201 78.00
M20x1.5	0201 80.00
M22x1.5	0201 82.00
M24x1.5	0201 83.00
M24x2	0201 92.00
M27x2	0201 86.00
M30x2	0201 88.00
M36x2	0201 93.00
M48x2	0201 98.00

内六角堵栓, 公制螺纹


0202



C	
M12x1	0202 65.00
M12x1.25	0202 66.00
M14x1.5	0202 71.00
M16x1.5	0202 75.00
M18x1.5	0202 78.00
M20x1.5	0202 80.00
M22x1.5	0202 82.00
M24x1.5	0202 83.00
M27x2	0202 86.00
M30x2	0202 88.00
M33x2	0202 91.00
M36x2	0202 93.00
M42x2	0202 96.00
M45x2	0202 97.00

四角堵栓, BSPT斜螺纹 (即PT斜螺纹)


0209



C	
R1/8	0209 10.00
R1/4	0209 13.00
R3/8	0209 17.00
R1/2	0209 21.00
R3/4	0209 27.00
R1 "	0209 34.00

内六角铜质堵栓, BSPT斜螺纹 (即PT斜螺纹) 及NPT螺纹

0205




G BSPT	
R1/8	0205 10.00
R1/4	0205 13.00
R3/8	0205 17.00
R1/2	0205 21.00
R3/4	0205 27.00
R1 "	0205 34.00
R1 " 1/4	0205 42.00
R1 " 1/2	0205 49.00
R2	0205 48.00

C NPT	
1/8	0205 11.00
1/4	0205 14.00
3/8	0205 18.00
1/2	0205 22.00
3/4	0205 28.00
1 "	0205 35.00

六角铜镀镍头附垫圈, BSPP直管螺纹

0222




C	
M5 x 0.8	0222 19.00
M7 x 1	0222 55.00
G1/8	0222 10.00
G1/4	0222 13.00
G3/8	0222 17.00
G1/2	0222 21.00

铁质及不锈钢堵栓

六角堵栓, BSPT斜螺纹 (即PT斜螺纹) 及NPT螺纹

0216




G BSPT	
R1/8	0216 10.00
R1/4	0216 13.00
R3/8	0216 17.00
R1/2	0216 21.00
R3/4	0216 27.00
R1 "	0216 34.00
R1 " 1/4	0216 42.00
R1 " 1/2	0216 49.00
R2 "	0216 48.00

C	
1/8	0216 11.00
1/4	0216 14.00
3/8	0216 18.00
1/2	0216 22.00
3/4	0216 28.00
1 "	0216 35.00
1 " 1/4	0216 43.00
1 " 1/2	0216 50.00
2 "	0216 44.00

一般铁质

内六角铜栓, BSPT斜螺纹 (即PT斜螺纹) 及NPT螺纹

0206




G BSPT	
R1/8	0206 10.00
R1/4	0206 13.00
R3/8	0206 17.00
R1/2	0206 21.00
R3/4	0206 27.00
R1 "	0206 34.00
R1 " 1/4	0206 42.00
R1 " 1/2	0206 49.00

C NPT	
1/16	0206 08.00
1/8	0206 11.00
1/4	0206 14.00
3/8	0206 18.00
1/2	0206 22.00
3/4	0206 28.00
1 "	0206 35.00

一般铁质

六角堵栓, BSPP直螺纹 (即PF直螺纹) 及公制螺纹

0210



C	
G1/8	0210 10.00
G1/4	0210 13.00
G3/8	0210 17.00
G1/2	0210 21.00
G3/4	0210 27.00
G1 "	0210 34.00
G1 " 1/4	0210 42.00
G1 " 1/2	0210 49.00
G2 "	0210 48.00

C	
M8x1.25	0210 57.00
M10x1	0210 60.00
M12x1	0210 65.00
M12x1.25	0210 66.00
M14x1.25	0210 70.00
M16x1.25	0210 74.00
M18x1.5	0210 78.00
M20x1.5	0210 80.00
M22x1.5	0210 82.00
M24x1.5	0210 83.00
M27x1.5	0210 85.00
M30x1.5	0210 87.00
M30x2	0210 88.00
M33x1.5	0210 90.00
M33x2	0210 91.00
M39x1.5	0210 36.00
M42x1.5	0210 37.00
M42x2	0210 96.00
M48x2	0210 98.00

一般铁质

内六角堵栓, BSPT斜螺纹 (即PT斜螺纹)

0285




C	
R1/8	0285 10.00
R1/4	0285 13.00
R3/8	0285 17.00
R1/2	0285 21.00

不锈钢AISI 316L

内六角堵栓, NPT螺纹

0285



C	
1/8	0285 11.00
1/4	0285 14.00
3/8	0285 18.00
1/2	0285 22.00

不锈钢AISI 316L

如需要各产品详细尺寸请与我们联系

铜质转接头

双外螺纹转接头

双外螺纹转接头, BSPT斜螺纹 (即PT斜螺纹)



C1	C2	
R1/8	R1/8	0121 10 10
R1/4	R1/4	0121 13 13
R1/4	R1/8	0121 13 10
R3/8	R3/8	0121 17 17
R3/8	R1/4	0121 17 13
R3/8	R1/8	0121 17 10
R1/2	R1/2	0121 21 21
R1/2	R3/8	0121 21 17
R1/2	R1/4	0121 21 13
R1/2	R1/8	0121 21 10
R3/4	R3/4	0121 27 27
R3/4	R1/2	0121 27 21
R3/4	R3/8	0121 27 17
R3/4	R1/4	0121 27 13
R1"	R1"	0121 34 34
R1"	R3/4	0121 34 27
R1"	R1/2	0121 34 21
R1"	R3/8"	0121 34 17
R1" 1/4	R1" 1/4	0121 42 42
R1" 1/4	R1"	0121 42 34
R1" 1/4	R3/4	0121 42 27
R1" 1/4	R1/2	0121 42 21

双外螺纹转接头, BSPT斜螺纹 (即PT斜螺纹)



C1	C2	
R1/8	R1/8	0121 10 10 85
R1/4	R1/8	0121 13 10 85
R1/4	R1/4	0121 13 13 85
R3/8	R1/4	0121 17 13 85
R3/8	R3/8	0121 17 17 85
R1/2	R3/8	0121 21 17 85
R1/2	R1/2	0121 21 21 85

*铜镀镍材质

PT(BSPT)外螺纹转PF(BSPP)外螺纹接头



C1	C2	
R1/8	G1/8	0192 10 13
R1/4	G1/4	0192 13 13
R1/4	G1/2	0192 13 21
R3/8	G1/4	0192 17 13
R3/8	G1/2	0192 17 21
R1/2	G1/2	0192 21 21

*铜镀镍材质

NPT外螺纹转PT(BSPT)外螺纹接头



C1	C2	
R1/8	R1/8	0121 11 10
R1/4	R1/4	0121 14 13
R3/8	R3/8	0121 18 17
R1/2	R1/2	0121 22 21
R3/4	R3/4	0121 28 27

不锈钢转接头

转接头, BSPP直螺纹 (即PF直螺纹)

双内螺纹直角接头



C	
G1/8	1843 10 10
G1/4	1843 13 13
G3/8	1843 17 17
G1/2	1843 21 21

内螺纹三通接头



C	
G1/8	1845 10 10
G1/4	1845 13 13
G3/8	1845 17 17
G1/2	1845 21 21

面板安装接头




C	
G1/8	1817 00 10
G1/4	1817 00 13
G3/8	1817 00 17
G1/2	1817 00 21

双内螺纹接头



C	
G1/8	1855 10 10
G1/4	1855 13 13
G3/8	1855 17 17
G1/2	1855 21 21

双内螺纹大转小接头



C1	C2	
G1/4	G1/8	1862 13 10
G3/8	G1/8	1862 17 10
G3/8	G1/4	1862 17 13
G1/2	G1/4	1862 21 13
G1/2	G3/8	1862 21 17


☒ = 不锈钢

不锈钢转接头

转接头, BSPT斜螺纹(即PT斜螺纹)及NPT罗纹

PT (BSPT) 外螺纹转NPT内螺纹接头


1867



C1	C2	
BSPT	NPT	
R1/8	1/8	1867 10 11
R1/4	1/4	1867 13 14
R3/8	3/8	1867 17 18
R1/2	1/2	1867 21 22

双外螺纹接头, BSPT斜螺纹(即PT斜螺纹)


1821



C1	C2	
R1/8	R1/8	1821 10 10
R1/4	R1/4	1821 13 13
R1/4	R1/8	1821 13 10
R3/8	R3/8	1821 17 17
R3/8	R1/4	1821 17 13
R1/2	R1/2	1821 21 21
R1/2	R3/8	1821 21 17

NPT外螺纹转PF (BSPP) 内螺纹接头


1864



C1	C2	
NPT	BSPT	
1/8	G1/8	1864 11 10
1/4	G1/4	1864 14 13
3/8	G3/8	1864 18 17
1/2	G1/2	1864 22 21

PT (BSPT) 外螺纹转PF (BSPP) 内螺纹接头


1863



C1	C2	
R1/4	G1/8	1863 13 10
R3/8	G1/8	1863 17 10
R3/8	G1/4	1863 17 13
R1/2	G1/4	1863 21 13
R1/2	G3/8	1863 21 17

等径双外螺纹转接头, NPT 螺纹


1821



C	
NPT	
1/8	1821 11 11
1/4	1821 14 14
3/8	1821 18 18
1/2	1821 22 22

PT (BSPT) 外螺纹转PF (BSPP) 内螺纹接头


1861



C1	C2	
R1/8	G1/4	1861 10 13
R1/8	G3/8	1861 10 17
R1/4	G3/8	1861 13 17
R1/4	G1/2	1861 13 21
R3/8	G1/2	1861 17 21

带管插转接头, BSPT即PT斜螺纹, 橡胶管用

1823




∅D	C	
7	R1/8	1823 07 10
7	R1/4	1823 07 13
10	R1/4	1823 10 13
10	R3/8	1823 10 17
13	R3/8	1823 13 17
16	R1/2	1823 16 21

不锈钢消音器-SUS316L

附外螺纹不锈钢消音器, BSPP直管螺纹


0682



C	
1/8	0682 00 10
1/4	0682 00 13
3/8	0682 00 17
1/2	0682 00 21
3/4	0682 00 27
1"	0682 00 34

附外螺纹不锈钢消音器, NPT 螺纹

0683




C	
1/8	0683 00 11
1/4	0683 00 14
3/8	0683 00 18
1/2	0683 00 22

产品编号编排方法

接头产品编号依据以下方式编列:


- 产品系列 (前4码)
- 插管管外径 (次2码)
- 外径或第二插管管外径 (再次2码)



消音器

带外螺纹消音器, BSPP直螺纹(即PF螺纹)及M5螺纹

0674



C	噪音值 (dBa at 6 bar)	
M5x0.8	86	0674 00 19
G1/8	80	0674 00 10
G1/4	85	0674 00 13
G3/8	84	0674 00 17
G1/2	84	0674 00 21
G3/4	85	0674 00 27
G1"	86	0674 00 34

PE材质

消音器带调速, BSPP直螺纹(即PF螺纹)

0676



C	
M5x0.8	0676 00 19
G1/8	0676 00 10
G1/4	0676 00 13
G3/8	0676 00 17
G1/2	0676 00 21

PE材质

带外螺纹消音器, BSPP直螺纹(即PF螺纹)及M5螺纹

0670



C	
G1/8	0670 00 10
G1/4	0670 00 13
G3/8	0670 00 17
G1/2	0670 00 21
G3/4	0670 00 27
G1"	0670 00 34

本体材质为黄铜
消音器为烧结青铜

流量 (升/分) 6 bar时	调整圈数									噪音值 dBA (6 bar, 350升/分)	
	技术资料										
	0	1	2	3	4	5	6	7	8		9
0676 00 19	0	22	69	97	125	143	-	-	-	-	81
0676 00 10	0	30	90	210	335	370	390	390	395	395	82
0676 00 13	0	22	25	50	340	750	940	980	1000	1025	84
0676 00 17	0	518	1147	1716	2153	2571	2823	2930	-	-	85
0676 00 21	0	814	1849	2880	4087	5044	5236	-	-	-	86

带外螺纹消音器, BSPP及M5螺纹

0673




C	
M5x0.8	0673 00 19
G1/8	0673 00 10
G1/4	0673 00 13
G3/8	0673 00 17
G1/2	0673 00 21

本体材质为黄铜
消音器为烧结青铜
最大工作压力12Bar

消音器带调速, BSPP直螺纹(即PF螺纹)

0672




C	
G1/8	0672 00 10
G1/4	0672 00 13
G3/8	0672 00 17
G1/2	0672 00 21

本体材质为黄铜
消音器为烧结青铜

带外螺纹消音器, BSPP直螺纹(即PF螺纹)及M5螺纹

0675




C	
M5x0.8	0675 00 19
G1/8	0675 00 10
G1/4	0675 00 13
G3/8	0675 00 17
G1/2	0675 00 21

本体材质为黄铜
消音器为烧结青铜

流量 (升/分) 6 bar时	调整圈数					噪音值 dBA (6 bar, 350升/分)	
	技术资料						
	0	1	2	3	4		5
0672 00 10	0	85	320	370	-	81	
0672 00 13	0	210	310	400	430	440	82
0672 00 17	0	305	690	1050	-	-	83
0672 00 21	0	411	1092	2152	-	-	83

铜电镀消音器, BSPP直管螺纹(即PF直螺纹)

0677



C	
1/8	0677 00 10
1/4	0677 00 13
3/8	0677 00 17
1/2	0677 00 21
3/4	0677 00 27
1"	0677 00 34

铜电镀材质

带尾插管消音器

0671



∅D	
4	0671 04 00
6	0671 06 00
8	0671 08 00
10	0671 10 00
12	0671 12 00

本体材质为黄铜
消音器为烧结青铜

消音器技术参数:

- 最大工作压力: 烧结青铜: 12 bar
PE 材质: 10 bar

- 最大温度: 烧结青铜: -20°C~+150°C
PE 材质: -10°C~+80°C

