


## HIGH COMMUTATION TRIAC

### T0220-AB



#### On-State Current      Gate Trigger Current

8 Amp

≤ 50 mA

#### Off-State Voltage

200 V ÷ 800 V

This series of TRIACs uses a high performance PNPN technology.

These parts are intended for general purpose AC switching applications with highly inductive loads.

### Absolute Maximum Ratings, according to IEC publication No. 134

SYMBOL	PARAMETER	CONDITIONS	Value	Unit
$I_{T(RMS)}$	RMS On-state Current (full sine wave)	All Conduction Angle, $T_C = 95^\circ\text{C}$	8	A
$I_{TSM}$	Non-repetitive On-State Current	Full Cycle, 60 Hz ( $t = 16.7\text{ ms}$ )	84	A
$I_{TSM}$	Non-repetitive On-State Current	Full Cycle, 50 Hz ( $t = 20\text{ ms}$ )	80	A
$I_{\zeta t}$	Fusing Current	$t_p = 10\text{ ms}$ , Half Cycle	32	A <sup>2</sup> s
$I_{GM}$	Peak Gate Current	20 $\mu\text{s}$ max. $T_j = 125^\circ\text{C}$	4	A
$P_{G(AV)}$	Average Gate Power Dissipation	$T_j = 125^\circ\text{C}$	1	W
$di/dt$	Critical rate of rise of on-state current	$I_G = 2 \times I_{GT}$ , $t_r \leq 100\text{ ns}$ $f = 120\text{ Hz}$ , $T_j = 125^\circ\text{C}$	50	A/ $\mu\text{s}$
$T_j$	Operating Temperature		(-40 +125)	$^\circ\text{C}$
$T_{stg}$	Storage Temperature		(-40 +150)	$^\circ\text{C}$
$T_{sld}$	Soldering Temperature	10s max	260	$^\circ\text{C}$

SYMBOL	PARAMETER	VOLTAGE					Unit
		B	D	M	S	N	
$V_{DRM}$	Repetitive Peak Off State Voltage	200	400	600	700	800	V
$V_{RRM}$							

## HIGH COMMUTATION TRIAC


### Electrical Characteristics

SYMBOL	PARAMETER	CONDITIONS	Quadrant		SENSITIVITY			Unit
					11	14	16	
$I_{GT}^{(1)}$	Gate Trigger Current	$V_D = 12 V_{DC}, R_L = 33\Omega, T_j = 25^\circ C$	Q1÷Q3	MAX	25	35	50	mA
$V_{GT}$	Gate Trigger Voltage	$V_D = 12 V_{DC}, R_L = 33\Omega, T_j = 25^\circ C$	Q1÷Q3	MAX	1.3			V
$V_{GD}$	Gate Non Trigger Voltage	$V_D = V_{DRM}, R_L = 3.3K\Omega, T_j = 125^\circ C$	Q1÷Q3	MIN	0.2			V
$I_H^{(2)}$	Holding Current	$I_T = 100 \text{ mA}, \text{ Gate open}, T_j = 25^\circ C$		MAX	25	35	50	mA
$I_L$	Latching Current	$I_G = 1.2 I_{GT}, T_j = 25^\circ C$	Q1, Q3	MAX	40	50	70	mA
			Q2	MAX	50	60	80	
$dV/dt^{(2)}$	Critical Rate of Voltage Rise	$V_D = 0.67 \times V_{DRM}, \text{ Gate open}$ $T_j = 125^\circ C$		MIN	200	500	1000	V/ $\mu s$
$(dI/dt)_c^{(2)}$	Critical Rate of Current Rise	$(dv/dt)_c = 0.1 \text{ V}/\mu s$ $(dv/dt)_c = 10 \text{ V}/\mu s$ without snubber $T_j = 125^\circ C$		MIN	-	-	-	A/ms
				MIN	-	-	-	
				MIN	4.0	4.5	7	
$V_{TM}^{(2)}$	On-state Voltage	$I_T = 11 \text{ Amp}, t_p = 380 \mu s, T_j = 25^\circ C$		MAX	1.6			V
$V_{T(O)}^{(2)}$	Threshold Voltage	$T_j = 125^\circ C$		MAX	0.85			V
$r_d^{(2)}$	Dynamic Resistance	$T_j = 125^\circ C$		MAX	70			m $\Omega$
$I_{DRM}/I_{RRM}$	Off-State Leakage Current	$V_D = V_{DRM}, T_j = 125^\circ C$ $V_R = V_{RRM}, T_j = 25^\circ C$		MAX	1			mA
				MAX	5			
$R_{th(j-c)}$	Thermal Resistance Junction-Case	for AC 360° conduction angle			1.6			$^\circ C/W$
$R_{th(j-a)}$					60			$^\circ C/W$

(1) Minimum  $I_{GT}$  is guaranteed at 5% of  $I_{GT}$  max.

(2) For either polarity of electrode MT2 voltage with reference to electrode MT1.

### PART NUMBER INFORMATION



## HIGH COMMUTATION TRIAC

Fig. 1: Maximum power dissipation versus RMS on-state current (full cycle)




Fig. 2: RMS on-state current versus case temperature (full cycle)




Fig. 3: Relative variation of thermal impedance versus pulse duration




Fig. 4: On-state characteristics (maximum values)




Fig. 5: Surge peak on-state current versus number of cycles





Fig. 6: Non repetitive surge peak on-state current for a sinusoidal pulse with width:  $t_p < 10$  ms, and corresponding value of  $I^2t$ .



## HIGH COMMUTATION TRIAC

Fig. 7: Relative variation of gate trigger current, holding current and latching versus junction temperature (typical values)






Fig. 8: Relative variation of critical rate of decrease of main current versus junction temperature



### PACKAGE MECHANICAL DATA

TO-220AB



REF.	DIMENSIONS	
	Milimeters	
	Min.	Max.
A	4.47	4.67
A1	1.17	1.37
A2	2.52	2.82
b	0.71	0.91
b2	1.17	1.37
c	0.31	0.53
D	14.65	15.35
D1	8.50	8.90
E	10.01	10.36
e	2.51	2.57
e1	4.98	5.18
H1	6.15	6.45
L	13.40	13.96
L1	3.56	3.96
P	3.735	3.935
Q	2.59	2.89

**Mounting Torque**

**1 N.m**

(\*) Limiting values and life support applications, see Web page.