

# iDialog



UPS VFD



Tower



**1:1** 400-1600 VA



USB plug



Plug & Play installation

## HIGHLIGHTS

- **Compact**
- **Silent operation**
- **Contemporary design**
- **Auto restart**
- **Low power consumption**

The iDialog range is the ideal solution for protecting PCs and peripherals in the home and office.

iDialog is easy to install and economic to run for protecting:

- IT equipment such as PCs, Media Centres and peripherals, TVs, Home Cinema systems, Satellite and Digital Terrestrial Receivers and DVD recorders and players;
- xDSL modems and routers;
- Small home appliances.

### Silent operation

The UPS is silent in operation (0dBA) thanks to its use of a fan-less design and high frequency components.

### Advanced communications

PowerShield<sup>3</sup> software allows for the safe shutdown of connected IT systems on mains power supply failure. PowerShield<sup>3</sup> provides efficient and intuitive UPS management using bar chart displays for important operating information.

### Auto restart

The UPS automatically restarts when the mains power supply is restored, after auto power.

### ECO Line environmental protection

With energy savings in mind, the iDialog range features a shut-off button to reduce energy consumption during periods of prolonged inactivity.

MODELS	IDG 400	IDG 600	IDG 800	IDG 1200	IDG 1600
<b>POWER</b>	400 VA/240 W	600 VA/360 W	800 VA/480 W	1200 VA/720 W	1600 VA/960 W
<b>INPUT</b>					
Nominal voltage	220-240 Vac				
Input voltage tolerance frequency	230 Vac (+20/-25%)				
Frequency	50/60 Hz with automatic selection				
<b>OUTPUT</b>					
Voltage during mains operation	230 Vac (+20/-25%)				
Voltage during battery operation	230 Vac (+/- 10%)				
Frequency during battery operation	50 or 60 Hz (+/- 1%)				
Waveform	Pseudo Sinusoidal				
<b>BATTERIES</b>					
Type	VRLA AGM maintenance-free lead based				
Recharge time	6-8 h				
<b>OTHER FEATURES</b>					
Net weight (kg)	3,2	3,4	6,6	6,9	
Gross weight (kg)	3,7	4,1	8,1	8,6	
Dimensions (WxDxH) (mm)	90 x 232 x 192			93 x 310 x 270	
Packaging dimensions (WxDxH) (mm)	138 x 300 x 278			170 x 400 x 370	
Protections	Excessive low battery - overvoltage - short circuit				
Communications	USB			USB + RS232	
Output sockets	4 IEC 320 C13			6 IEC 320 C13	
Standards	EN 62040-1-1 and Directive 2006/95/EC; EN 62040-3 EN 62040-2 and Directive 2004/108 EC				
Certificates	CE				
Operating temperature	0 °C / +40 °C				
Colour	Black				
Altitude and relative humidity	6000 m max altitude, <95% non-condensing				
Standard equipment	2 output power supply cables, user manual				

## Features

- Reduced energy consumption and 99% efficiency
- Maximum reliability and protection of PCs thanks to PowerShield<sup>3</sup> monitoring and shutdown software, which can be downloaded free at [www.riello-ups.com](http://www.riello-ups.com)
- Can be installed on PCs with Windows operating systems 8, 7, Hyper-V, 2012, 2008, and previous versions, Mac OS X, Linux.
- Small size: With its compact shape, iDialog can be placed anywhere on the desk or in the home.
- Silent: iDialog is also suitable for protecting your non-professional digital

equipment such as home cinema systems, satellite and digital terrestrial receivers and DVD players/recorders.

## 2-YEAR WARRANTY

## AVAILABLE OPTIONS

### SOFTWARE

PowerShield<sup>3</sup>

## DETAILS

